

## **Certification Report**

## BSI-DSZ-CC-1107-V5-2024

for

IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance

from

Infineon Technologies AG

BSI - Bundesamt für Sicherheit in der Informationstechnik, Postfach 20 03 63, D-53133 Bonn Phone +49 (0)228 99 9582-0, Fax +49 (0)228 9582-5477, Infoline +49 (0)228 99 9582-111

Certification Report V1.0 CC-Zert-327 V5.47





#### BSI-DSZ-CC-1107-V5-2024 (\*)

IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance



SOGIS Recognition Agreement

from Infineon Technologies AG

PP Conformance: Security IC Platform Protection Profile with

Augmentation Packages Version 1.0, 13 January

2014, BSI-CC-PP-0084-2014

Functionality: PP conformant plus product specific extensions

Common Criteria Part 2 extended


Assurance: Common Criteria Part 3 conformant

EAL 6 augmented by ALC FLR.1

valid until: 4 December 2028

Common Criteria

The IT Product identified in this certificate has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by Scheme Interpretations by advice of the Certification Body for components beyond EAL 5 and CC Supporting Documents as listed in the Certification Report for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1. CC and CEM are also published as ISO/IEC 15408 and ISO/IEC 18045.



The evaluation has been conducted in accordance with the provisions of the certification scheme of the German Federal Office for Information Security (BSI) and the conclusions of the evaluation facility in the evaluation technical report are consistent with the evidence adduced.

This certificate is not an endorsement of the IT Product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT Product by the Federal Office for Information Security or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.



Common Criteria Recognition Arrangement recognition for components up to EAL 2 and ALC\_FLR only

Bonn, 4 September 2024

For the Federal Office for Information Security

Sandro Amendola Director-General

L.S.



This page is intentionally left blank.

## **Contents**

| A. Certification  | 6           |
|---|-------------|
| Preliminary Remarks     Specifications of the Certification Procedure     Recognition Agreements     Performance of Evaluation and Certification     Validity of the Certification Result     Publication   | 6<br>8<br>8 |
| B. Certification Results  | 10          |
| <ol> <li>Executive Summary.</li> <li>Identification of the TOE.</li> <li>Security Policy.</li> <li>Assumptions and Clarification of Scope.</li> <li>Architectural Information.</li> <li>Documentation.</li> <li>IT Product Testing.</li> <li>Evaluated Configuration.</li> <li>Results of the Evaluation.</li> <li>Obligations and Notes for the Usage of the TOE.</li> <li>Security Target.</li> <li>Regulation specific aspects (eIDAS, QES).</li> <li>Definitions.</li> <li>Bibliography.</li> </ol> |             |
| C. Excerpts from the Criteria   | 37          |
| D Annexes   | 38          |

#### A. Certification

## 1. Preliminary Remarks

Under the BSIG¹ Act, the Federal Office for Information Security (BSI) has the task of issuing certificates for information technology products.

Certification of a product is carried out on the instigation of the vendor or a distributor, hereinafter called the sponsor.

A part of the procedure is the technical examination (evaluation) of the product according to the security criteria published by the BSI or generally recognised security criteria.

The evaluation is normally carried out by an evaluation facility recognised by the BSI or by BSI itself.

The result of the certification procedure is the present Certification Report. This report contains among others the certificate (summarised assessment) and the detailed Certification Results.

The Certification Results contain the technical description of the security functionality of the certified product, the details of the evaluation (strength and weaknesses) and instructions for the user.

## 2. Specifications of the Certification Procedure

The certification body conducts the procedure according to the criteria laid down in the following:

- Act on the Federal Office for Information Security<sup>1</sup>
- BSI Certification and Approval Ordinance<sup>2</sup>
- BMI Regulations on Ex-parte Costs<sup>3</sup>
- Special decrees issued by the Bundesministerium des Innern und für Heimat (Federal Ministry of the Interior and Community)
- DIN EN ISO/IEC 17065 standard
- BSI certification: Scheme documentation describing the certification process (CC-Produkte) [3]
- BSI certification: Scheme documentation on requirements for the Evaluation Facility, its approval and licencing process (CC-Stellen) [3]
- Common Criteria for IT Security Evaluation (CC), Version 3.1<sup>4</sup> [1] also published as ISO/IEC 15408
- Act on the Federal Office for Information Security (BSI-Gesetz BSIG) of 14 August 2009, Bundesgesetzblatt I p. 2821
- Ordinance on the Procedure for Issuance of Security Certificates and approval by the Federal Office for Information Security (BSI-Zertifizierungs- und -Anerkennungsverordnung BSIZertV) of 17 December 2014, Bundesgesetzblatt 2014, part I, no. 61, p. 2231
- BMI Regulations on Ex-parte Costs Besondere Gebührenverordnung des BMI für individuell zurechenbare öffentliche Leistungen in dessen Zuständigkeitsbereich (BMIBGebV), Abschnitt 7 (BSI-Gesetz) - dated 2 September 2019, Bundesgesetzblatt I p. 1365

 Common Methodology for IT Security Evaluation (CEM), Version 3.1 [2] also published as ISO/IEC 18045

• BSI certification: Application Notes and Interpretation of the Scheme (AIS) [4]

## 3. Recognition Agreements

In order to avoid multiple certification of the same product in different countries a mutual recognition of IT security certificates - as far as such certificates are based on ITSEC or CC - under certain conditions was agreed.

## 3.1. European Recognition of CC – Certificates (SOGIS-MRA)

The SOGIS-Mutual Recognition Agreement (SOGIS-MRA) Version 3 became effective in April 2010. It defines the recognition of certificates for IT-Products at a basic recognition level and, in addition, at higher recognition levels for IT-Products related to certain SOGIS Technical Domains only.

The basic recognition level includes Common Criteria (CC) Evaluation Assurance Levels EAL 1 to EAL 4. For "Smartcards and similar devices" a SOGIS Technical Domain is in place. For "HW Devices with Security Boxes" a SOGIS Technical Domains is in place, too. In addition, certificates issued for Protection Profiles based on Common Criteria are part of the recognition agreement.

The current list of signatory nations and approved certification schemes, details on recognition, and the history of the agreement can be seen on the website at <a href="https://www.sogis.eu">https://www.sogis.eu</a>.

The SOGIS-MRA logo printed on the certificate indicates that it is recognised under the terms of this agreement by the related bodies of the signatory nations. A disclaimer beneath the logo indicates the specific scope of recognition.

This certificate is recognized under SOGIS-MRA for all assurance components selected.

#### 3.2. International Recognition of CC - Certificates (CCRA)

The international arrangement on the mutual recognition of certificates based on the CC (Common Criteria Recognition Arrangement, CCRA-2014) has been ratified on 08 September 2014. It covers CC certificates based on collaborative Protection Profiles (cPP) (exact use), CC certificates based on assurance components up to and including EAL 2 or the assurance family Flaw Remediation (ALC\_FLR) and CC certificates for Protection Profiles and for collaborative Protection Profiles (cPP).

The current list of signatory nations and approved certification schemes can be seen on the website: <a href="https://www.commoncriteriaportal.org">https://www.commoncriteriaportal.org</a>.

The Common Criteria Recognition Arrangement logo printed on the certificate indicates that this certification is recognised under the terms of this agreement by the related bodies of the signatory nations. A disclaimer beneath the logo indicates the specific scope of recognition.

This certificate is recognized according to the rules of CCRA-2014, i. e. up to and including CC part 3 EAL 2 and ALC\_FLR components.

<sup>&</sup>lt;sup>4</sup> Proclamation of the Bundesministerium des Innern und für Heimat of 12 February 2007 in the Bundesanzeiger dated 23 February 2007, p. 3730

#### 4. Performance of Evaluation and Certification

The certification body monitors each individual evaluation to ensure a uniform procedure, a uniform interpretation of the criteria and uniform ratings.

The product IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance has undergone the certification procedure at BSI. This is a re-certification based on BSI-DSZ-CC-1107-V4-2023. Specific results from the evaluation process BSI-DSZ-CC-1107-V4-2023 were re-used.

The evaluation of the product IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance was conducted by TÜV Informationstechnik GmbH. The evaluation was completed on 3 September 2024. TÜV Informationstechnik GmbH is an evaluation facility (ITSEF)<sup>5</sup> recognised by the certification body of BSI.

For this certification procedure the sponsor and applicant is: Infineon Technologies AG.

The product was developed by: Infineon Technologies AG.

The certification is concluded with the comparability check and the production of this Certification Report. This work was completed by the BSI.

## 5. Validity of the Certification Result

This Certification Report applies only to the version of the product as indicated. The confirmed assurance package is valid on the condition that

- all stipulations regarding generation, configuration and operation, as given in the following report, are observed,
- the product is operated in the environment described, as specified in the following report and in the Security Target.

For the meaning of the assurance components and assurance levels please refer to CC itself. Detailed references are listed in part C of this report.

The Certificate issued confirms the assurance of the product claimed in the Security Target at the date of certification. As attack methods evolve over time, the resistance of the certified version of the product against new attack methods needs to be re-assessed. Therefore, the sponsor should apply for the certified product being monitored within the assurance continuity program of the BSI Certification Scheme (e.g. by a re-assessment or re-certification). Specifically, if results of the certification are used in subsequent evaluation and certification procedures, in a system integration process or if a user's risk management needs regularly updated results, it is recommended to perform a re-assessment on a regular e.g. annual basis.

<sup>&</sup>lt;sup>5</sup> Information Technology Security Evaluation Facility

In order to avoid an indefinite usage of the certificate when evolved attack methods would require a re-assessment of the products resistance to state of the art attack methods, the maximum validity of the certificate has been limited. The certificate issued on 4 September 2024 is valid until 4 December 2028. Validity can be re-newed by re-certification.

The owner of the certificate is obliged:

- when advertising the certificate or the fact of the product's certification, to refer to the Certification Report as well as to provide the Certification Report, the Security Target and user guidance documentation mentioned herein to any customer of the product for the application and usage of the certified product,
- 2. to inform the Certification Body at BSI immediately about vulnerabilities of the product that have been identified by the developer or any third party after issuance of the certificate,
- 3. to inform the Certification Body at BSI immediately in the case that security relevant changes in the evaluated life cycle, e.g. related to development and production sites or processes, occur, or the confidentiality of documentation and information related to the Target of Evaluation (TOE) or resulting from the evaluation and certification procedure where the certification of the product has assumed this confidentiality being maintained, is not given any longer. In particular, prior to the dissemination of confidential documentation and information related to the TOE or resulting from the evaluation and certification procedure that do not belong to the deliverables according to the Certification Report part B, or for those where no dissemination rules have been agreed on, to third parties, the Certification Body at BSI has to be informed.

In case of changes to the certified version of the product, the validity can be extended to the new versions and releases, provided the sponsor applies for assurance continuity (i.e. re-certification or maintenance) of the modified product, in accordance with the procedural requirements, and the evaluation does not reveal any security deficiencies.

#### 6. Publication

The product IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance has been included in the BSI list of certified products, which is published regularly (see also Internet: <a href="https://www.bsi.bund.de">https://www.bsi.bund.de</a> and [5]). Further information can be obtained from BSI-Infoline +49 228 9582-111.

Further copies of this Certification Report can be requested from the developer of the product. The Certification Report may also be obtained in electronic form at the internet address stated above.

### **B.** Certification Results

The following results represent a summary of

- the Security Target of the sponsor for the Target of Evaluation,
- the relevant evaluation results from the evaluation facility, and
- complementary notes and stipulations of the certification body.

## 1. Executive Summary

The Target of Evaluation (TOE) is the Infineon Security Controller IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance.

The TOE provides a 32-bit ARMv7-M CPU-architecture. The major components of the core system are the CPU (Central Processing Unit), an MPU (Memory Protection Unit), a Nested Vectored Interrupt Controller (NVIC) and an Instruction Stream Signature (ISS). The dual interface controller is able to communicate using either the contact based or the contactless interface.

This TOE is intended to be used in smart cards for particular security relevant applications and as a developing platform for smart card operating systems. The term smartcard embedded software is used in the following for all operating systems and applications stored and executed on the TOE. The TOE is the platform for the smartcard embedded software.

The TOE Security Assurance Requirements (SAR) are based entirely on the assurance components defined in Part 3 of the Common Criteria (see part C or [1], Part 3 for details). The TOE meets the assurance requirements of the Evaluation Assurance Level EAL 6 augmented by ALC FLR.1.

The TOE Security Functional Requirements (SFR) relevant for the TOE are outlined in the Security Target [6] and [9], chapter 6. They are selected from Common Criteria Part 2 and some of them are newly defined. Thus the TOE is CC Part 2 extended.

The TOE Security Functional Requirements are implemented by the following TOE Security Functionality:

| TOE Security Functionality | Addressed issue                      |
|----------------------------|--------------------------------------|
| SF_DPM                     | Device Phase Management              |
| SF_PS                      | Protection against Snooping          |
| SF_PMA                     | Protection against Modifying Attacks |
| SF_PLA                     | Protection against Logical Attacks   |
| SF_CS                      | Cryptographic Support                |

Table 1: TOE Security Functionalities

For more details please refer to the Security Target [6] and [9], chapter 7.

The assets to be protected by the TOE are defined in the Security Target [6] and [9], chapter 3.1.2. Based on these assets the TOE Security Problem is defined in terms of Assumptions, Threats and Organisational Security Policies. This is outlined in the Security Target [6] and [9], chapter 3.

This certification covers the configurations of the TOE as outlined in chapter 8.

The vulnerability assessment results as stated within this certificate do not include a rating for those cryptographic algorithms and their implementation suitable for encryption and decryption (see BSIG Section 9, Para. 4, Clause 2).

The certification results only apply to the version of the product indicated in the certificate and on the condition that all the stipulations are kept as detailed in this Certification Report. This certificate is not an endorsement of the IT product by the Federal Office for Information Security (BSI) or any other organisation that recognises or gives effect to this certificate, and no warranty of the IT product by BSI or any other organisation that recognises or gives effect to this certificate, is either expressed or implied.

#### 2. Identification of the TOE

The Target of Evaluation (TOE) is called:

IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance.

The following table outlines the TOE deliverables:

| No | Туре | Identifier  | Release   | Form of Delivery   |
|----|------|---|---|--|
| 1. | HW   | IFX_CCI_00002Dh, IFX_CCI_000039h, IFX_CCI_00003Ah, IFX_CCI_000044h, IFX_CCI_000045h, IFX_CCI_000046h, IFX_CCI_000047h, IFX_CCI_000048h, IFX_CCI_00004Bh, IFX_CCI_00004Bh, IFX_CCI_00004Ch, IFX_CCI_00004Dh, IFX_CCI_00004Eh | T11   | Postal transfer in cages as complete modules, wafers, IC cases or packages |
| 2. | FW   | BOS, RFAPI (ROM part) & POWS  | 80.306.16.0 or<br>80.306.16.1 or<br>80.312.02.0           |  |
| 3. | FW   | Flash Loader  | 09.12.0005 or 09.14.0002                                  | Stored on the delivered hardware   |
| 4. | sw   | NRG™ SW (optional)  | v05.03.4097   | Secure download (L251 Library File) via ishare.                            |
| 5. | SW   | HSL (optional)  | v3.52.9708  | Secure download (L251 Library File) via ishare.                            |
| 6. | sw   | UMSLC   | v01.30.0564   | Stored on the delivered hardware.  |
| 7. | sw   | SCL (optional)  | v2.15.000 or<br>v2.11.003                                 | Secure download (L251 Library File) via ishare.                            |
| 8. | SW   | ACL (optional)  | v3.35.001 or<br>v3.34.000 or<br>v3.33.003 or<br>v3.02.000 | Secure download (L251 Library File) via ishare.                            |
| 9. | sw   | RCL (optional)  | v1.10.007   | Secure download (L251 Library File) via ishare.                            |

| No      | Туре | Identifier  | Release                    | Form of Delivery                                |
|---------|------|---|----------------------------|---|
| 10.     | SW   | HCL (optional)  | v1.13.002                  | Secure download (L251 Library File) via ishare. |
| 11.     | DOC  | 32-bit Security Controller - V11,<br>Hardware Reference Manual  | 2020-12-21<br>v6.2         | Personalized PDF via secure iShare server.      |
| 12.     | DOC  | SLx1/SLx3 (40 nm) Security Controllers, Programmer's Reference Manual                                   | 2023-07-06<br>v5.6         | Personalized PDF via secure iShare server.      |
| 13      | DOC  | 32-bit Security Controller - V11, Security Guidelines   | 2023-06-19<br>v1.00-2976   | Personalized PDF via secure iShare server.      |
| 14      | DOC  | Production and personalization, 32-bit security controller (Flash Loader 09.12.0005)                    | 2023-03-02<br>v9.12        | Personalized PDF via secure iShare server.      |
| 15      | DOC  | SLx3 (40 nm) Security Controllers<br>Production and Personalization Manual<br>(Flash Loader 09.14.0002) | 2023-07-21<br>v9.14        | Personalized PDF via secure iShare server.      |
| 16      | DOC  | 32-bit Security Controller Crypto2304T V3, User Manual (optional)                                       | 2024-06-21<br>v3.0         | Personalized PDF via secure iShare server.      |
| 17      | DOC  | HSL SLCx7 V11, Hardware Support Library (optional)  | 2021-01-25<br>03.52.9708   | Personalized PDF via secure iShare server.      |
| 18      | DOC  | UMSLC library for SLCx7 in 40nm   | V01.30.0564,<br>2019-06-19 | Personalized PDF via secure iShare server.      |
| 19      | DOC  | SCL37-SCP-v440-C40<br>Symmetric Crypto Library for SCP-v440<br>AES/DES/MAC<br>(optional)                | 2021-06-16<br>v2.11.003    | Personalized PDF via secure iShare server.      |
| 20      | DOC  | SCL37-SCP-v440-C40<br>Symmetric Crypto Library for SCP-v440<br>AES/DES/MAC<br>(optional)                | 2023-07-20<br>v2.15.000    | Personalized PDF via secure iShare server.      |
| 21      | DOC  | ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox (optional)              | 2024-08-16<br>v3.02.000    | Personalized PDF via secure iShare server.      |
| 22      | DOC  | ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox (optional)              | 2024-08-16<br>v3.33.003    | Personalized PDF via secure iShare server.      |
| 23<br>a | DOC  | ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox (optional)              | 2024-08-16<br>v3.34.000    | Personalized PDF via secure iShare server.      |
| 23<br>b | DOC  | ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox (optional)              | 2024-06-06<br>v3.35.001    | Personalized PDF via secure iShare server.      |

| No | Туре | Identifier  | Release  | Form of Delivery                           |
|----|------|---|----------|--|
| 24 | DOC  | RCL37-X-C40 Random Crypto Library<br>for SCP-v440 & RNG-v3<br>DRBG/HWRNG 32-bit Security<br>Controller, User interface manual<br>(optional) | 1.10.007 | Personalized PDF via secure iShare server. |
| 25 | DOC  | HCL37-CPU-C40 Hash Crypto Library for CPU SHA 32-bit Security Controller, User interface manual (optional)                                  |          | Personalized PDF via secure iShare server. |

Table 2: Deliverables of the TOE

Please note that NRG functionality and most toolbox functionality are out of scope of this evaluation (unless stated otherwise), hence no evaluated TOE guidance documentation applies. However, respective developer provided documentation may be available. User discretion is advised.

The delivery documentation describes all procedures that are necessary to maintain security when distributing versions of the TOE or parts of it to the user's site including the necessary intermediate delivery procedures.

Furthermore, the delivery documentation describes in a sufficient manner how the various procedures and technical measures provide for the detection of modifications and any discrepancies between the TOE respective parts of it sent by the TOE Manufacturer and the version received by the Composite Product Manufacturer.

Three different delivery procedures have to be taken into consideration:

- Delivery of the IC dedicated software components (IC dedicated SW, guidance) from the TOE Manufacturer to the IC Embedded Software Developer.
- Delivery of the IC Embedded Software (ROM / Flash data, initialisation and prepersonalisation data) from the IC Embedded Software Developer to the TOE Manufacturer.
- Delivery of the final TOE from the TOE Manufacturer to the Composite Product Manufacturer. After phase 3 the TOE is delivered in form of wafers or sawn wafers, after phase 4 in form of modules (with or without inlay antenna) or any other packaging form as offered.

Respective distribution centers are listed in Appendix B (see end of document).

The individual TOE hardware is uniquely identified by its identification data. Each individual TOE can therefore be traced unambiguously and thus assigned to the entire development and production process.

The hardware part of the TOE is identified by IFX\_CCI\_00002Dh, IFX\_CCI\_000039h, IFX\_CCI\_00003Ah, IFX\_CCI\_000044h, IFX\_CCI\_000045h, IFX\_CCI\_000046h, IFX\_CCI\_000047h, IFX\_CCI\_000048h, IFX\_CCI\_00004Ph, IFX\_CCI\_00004Ah, IFX\_CCI\_00004Ch, IFX\_CCI\_00004Dh, IFX\_CCI\_00004Eh design step T11.

Another characteristic of the TOE are the chip identification data. These chip identification data is accessible via the Generic Chip Identification Mode (GCIM) (see [12], section 4.5).

At TOE start-up the so called GCIM can be chosen by applying special signalling in contactless or contact based communication and the TOE outputs then the generic chip identification data (unless another configuration option is chosen). This data contain the

firmware identifier accompanied with the certification identifier, the design step and even more tracking information. In combination with [12] (section 4.5) the user can identify the data, interpret it and retrieve the TOE versioning information. This information includes also the required mapping of firmware identifier and certification identifier.

The optional software libraries can be identified by their unique version numbers and by calculating a hash value (e.g. SHA-256) over the delivered lib-files (.lib) and comparing the calculated values to the values stated in Security Target [6] and Security Target Lite [9], sections 9 - 15.

## 3. Security Policy

The Security Policy is expressed by the set of Security Functional Requirements and implemented by the TOE. It covers the following issues:

The security policy of the TOE is to provide basic security functionalities to be used by the smart card operating system and the smart card application, thus providing an overall smart card system security. Therefore, the TOE will implement a symmetric cryptographic block cipher algorithm (Triple-DES and AES) to ensure the confidentiality of plain text data by encryption and to support secure authentication protocols and it will provide a different random number generators.

The RSA library is used to provide a high-level interface to RSA (Rivest, Shamir, Adleman) cryptography implemented on the hardware component Crypto@2304T and includes countermeasures against SPA, DPA and DFA attacks. The EC library is used to provide a high-level interface to Elliptic Curve cryptography implemented on the hardware component Crypto@2304T and includes countermeasures against SPA, DPA and DFA attacks. The optional Hash Crypto Library provides a high-level interface for performing cryptographic hash functions and includes countermeasures against SPA, DPA and DFA attacks. The RCL provides a high-level interface for obtaining random data. This can be deterministic data from an AES CTR\_DRBG or non-deterministic data that is provided by the underlying hardware. The RCL includes countermeasures against SPA, DPA and DFA attacks.

Besides that, the TOE can come with the optional Hardware Support Library (HSL) providing a simplified interface for NVM management and provides the possibility to write tearing safe into the NVM.

As the TOE is a hardware security platform, the security policy of the TOE is also to provide protection against leakage of information (e.g. to ensure the confidentiality of cryptographic keys during AES, Triple-DES, RSA and EC cryptographic functions performed by the TOE), against physical probing, against malfunctions, against physical manipulations and against abuse of functionality. Hence, the TOE shall

- maintain the integrity and the confidentiality of data stored in the memory of the TOE, and
- maintain the integrity, the correct operation and the confidentiality of security functionalities (security mechanisms and associated functions) provided by the TOE.

Specific details concerning the above mentioned security policies can be found in sections 6 and 7 of the Security Target [6] and [9].

## 4. Assumptions and Clarification of Scope

The Assumptions defined in the Security Target and some aspects of Threats and Organisational Security Policies are not covered by the TOE itself. These aspects lead to specific security objectives to be fulfilled by the TOE-Environment. The following topics are of relevance:

The objective OE.Resp-Appl states that the IC embedded software developer shall treat user data (especially keys) of the composite product appropriately. The IC embedded software developer gets sufficient information on how to protect user data adequately in the security guidelines [14].

The ST includes the following security objectives for the operational environment, which are relevant for the Composite Product Manufacturer: OE.Process-Sec-IC, OE.Lim\_Block\_Loader, OE.Loader\_Usage, OE.TOE\_Auth, OE.Secure\_Load\_ACode, and OE.Prevent Masquerade.

The objective OE.Process-Sec-IC requires the protection of the TOE, as well as of its manufacturing and test data up to the delivery to the end-consumer. As defined in [6],[9] Chapter 1.4.5 the TOE can be delivered to the composite product manufacturer after phase 3 or after phase 4. However, the single chips are identical in all cases. This means that the test mode is deactivated and the TOE is locked in the user mode. Therefore, it is not necessary to distinguish between these forms of delivery. Since Infineon has no information about the security requirements of the implemented IC embedded software it is not possible to define any concrete security requirements for the environment of the composite product manufacturer.

The objective OE.TOE\_Auth requires that the environment has to support the authentication and verification mechanism and has to know the corresponding authentication reference data. The composite product manufacturer receives sufficient information with regard to the authentication mechanism in [15], chapter 2.1.5 / [26], chapter 2.1.8. Please note that this objective is only valid in case the Flash Loader is ordered with mutual authentication (i.e., option External Authentication is unavailable).

The objective OE.Secure\_Load\_ACode is only applicable in life cycle phase 7 and in case of Flash Loader v09.14.0002. In this case the user software is required to support the secure image loading (during phase 7/in-field update) by providing the relevant key material for the image.

The objective OE.Prevent\_Masquerade is valid in case the Flash Loader is ordered with External Authentication (EA) instead of mutual authentication. In this case, customers need to take care that not masquerading attacks can be performed. The objective replaces OE.Prevent\_Masquerade. A description of the External Authentication is given in [15] chapter 2.1.5 and further highlights the risks of masquerading attacks when using this order option of the flash loader:

The objective OE.Prevent\_Masquerade is valid in case the Flash Loader is ordered with External Authentication (EA) instead of a mutual authentication. In this case, customers need to take care that not masquerading attacks can be performed.

The objective OE.Loader\_Usage requires that the authorised user has to support the trusted communication with the TOE by protecting the confidentiality and integrity of the loaded data and he has to meet the access conditions defined by the flash loader. [15], chapter 4 / [26], chapter 4 provides sufficient information regarding this topic.

The objective OE.Lim\_Block\_Loader requires the composite product manufacturer to protect the loader against misuse, to limit the capability of the loader and to terminate the loader irreversibly after the intended usage. The permanent deactivation of the flash loader is described in [15], chapter 2.1.2.2 / [26], chapter 2.1.4.2. This objective for the environment originates from the "Package 1: Loader dedicated for usage in secured environment only". However, this TOE also implements "Package 2: Loader dedicated for usage by authorized users only" and thus the flash loader can also be used in an unsecure environment and is able to protect itself against misuse if the authentication and download keys are handled appropriately.

#### 5. Architectural Information

For further information on the TOE architecture, see Security Target [6] and [9], section 1 (especially sections 1.3 and 1.4).

#### 6. Documentation

The evaluated documentation as outlined in table 2 is being provided with the product to the customer. This documentation contains the required information for secure usage of the TOE in accordance with the Security Target.

Additional obligations and notes for secure usage of the TOE as outlined in chapter 10 of this report have to be followed.

## 7. IT Product Testing

#### Regarding functional testing:

Different classes of functional tests were performed by the developer to test the TOE:

- Simulation tests (design verification),
- Qualification tests.
- Verification Tests.
- Security functional Tests,
- Production Tests.

The developer's testing results demonstrate that the TSFs behave as specified. The developer's testing results also demonstrate that the TOE behaves as expected.

In the course of the evaluation of the TOE, the following classes of functional tests were carried out by the ITSEF:

- Module tests,
- Simulation tests,
- Emulation tests,
- Tests in user mode,
- Tests in test mode,
- Hardware tests,
- Optional library tests,

repetition of developer tests (see above).

With these kinds of tests the entire security functionality of the TOE was tested.

The results of the (functional) developer tests, which have been repeated by the evaluator, matched the results the developer stated.

Overall, the TSF has been tested against the functional specification, the TOE design and the security architecture description. The tests demonstrate that the TSF performs as specified.

#### Regarding AVA related tests:

The penetration testing was partially performed using the developer's testing environment, partially using the test environment of the evaluation body.

All configurations of the TOE being intended to be covered by the current evaluation were tested.

The overall test result is that no deviations were found between the expected and the actual test results. No attack scenario with the attack potential high was successful in the TOE's operational environment as defined in [ST], provided that all measures required by the developer are applied.

The embedded software must implement the security advice given in [12] – [28] (if applicable).

## 8. Evaluated Configuration

In the broadest sense, the production of the mask sets for the chip production may be looked upon as the procedure for the system generation. The TOE can be delivered in the following configuration:

This TOE is represented by various configurations called products. The module design, layout and footprint, of all products are identical. The degree of freedom for configuring the TOE is predefined by the developer.

Furthermore the TOE is comprised of firmware and optional software libraries with revisions stated in section 2. The flash loader (part of FW) was enabled on evaluated derivatives.

An extensive overview over all possible configuration options is given in the Security Target [6] and [9] in sections 1.4.5 and 1.4.7.

The evaluation results, also including results of tests performed by the developer, are valid for all hardware derivates mentioned above. All identifiers represent the equal hardware platform but name differences in configurations or market segments. Configuration differences are achieved by blocking only. The firmware and optional software libraries were examined in those revisions, which are stated in table 2 (above).

The evaluation results are valid for all configurations and blocking options of the hardware stated in section 1.4.7 of the Security Target [6] and [9]. Depending on configuration, blocking option and on selection of optional software libraries, some of the services might be unavailable to the user. The unavailable services have no security impact on the TOE.

The user must ensure a working configuration. The evaluation results apply to all configurations of Flash Loader, BPU and PIN-Letter as stated in the Security Target [6] and [9].

The evaluation results cannot be extended to further versions/derivates of the TOE and/or other production sites without any extra investigations.

Developer and evaluator tested the TOE in these configurations in which the TOE is delivered and which is described above and in Section 2.

#### 9. Results of the Evaluation

#### 9.1. CC specific results

The Evaluation Technical Report (ETR) [7] was provided by the ITSEF according to the Common Criteria [1], the Methodology [2], the requirements of the Scheme [3] and all interpretations and guidelines of the Scheme (AIS) [4] as relevant for the TOE.

The Evaluation Methodology CEM [2] was used for those components up to EAL 5 extended by advice of the Certification Body for components beyond EAL 5 and guidance specific for the technology of the product [4] (AIS 34).

The following guidance specific for the technology was used:

- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 1, Durchführung der Ortsbesichtigung in der Entwicklungsumgebung des Herstellers, Version 14, 2017-10-11, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 14, Anforderungen an Aufbau und Inhalt der ETR-Teile (Evaluation Technical Report) für Evaluationen nach CC (Common Criteria), Version 7, 2010-08-03, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 19, Anforderungen an Aufbau und Inhalt der Zusammenfassung des ETR (Evaluation Technical Report) für Evaluationen nach CC (Common Criteria), Version 9, 2014-11-03, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 20, Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren, Version 3, 2013-05-15, Herausgeber: Zertifizierungsstelle des BSI im Rahmen des Zertifizierungsschemas, Bundesamt für Sicherheit in der Informationstechnik.
- A proposal for: Functionality classes for random number generators, W. Killmann, W. Schindler, Version 2.0, 2011-09-18, T-Systems GEI GmbH and Bundesamt für Sicherheit in der Informationstechnik. (same as [AIS31\_KS2011])
- Developer evidence for the evaluation of a deterministic random number generator,
   Version 0.9, 2013-02-28, Bundesamt für Sicherheit in der Informationstechnik.
- Evaluation Report as part of the Evaluation Technical Report, Part B ETR-Part Deterministic Random Number Generator, Template-Version 0.10, 2013-02-28, Bundesamt für Sicherheit in der Informationstechnik.
- CC Supporting Document Guidance Collection of Developer Evidence, Version 1.5, April 2012, CCDB-2012-04-005.

 Joint Interpretation Library – Collection of Developer Evidence, Version 1.5, January 2012.

- Application Notes and Interpretation of the Scheme (AIS) AIS 25, Anwendungen der CC auf integrierte Schaltungen, Version 9, 2017-03-15, Bundesamt für Sicherheit in der Informationstechnik.
- CC Supporting Document Mandatory Technical Document Security Architecture requirements (ADV\_ARC) for smart cards and similar devices, Version 2.1, April 2014, CCDB-2012-04-004.
- CC Supporting Document Guidance Security Architecture requirements (ADV\_ARC) for smart cards and similar devices Appendix 1, Version 2.0, April 2012.
- CC Supporting Document Mandatory Technical Document The Application of CC to Integrated Circuits, Version 3.0, Revision 1, March 2009, CCDB-2009-03-002.
- Joint Interpretation Library Security Architecture requirements (ADV\_ARC) for smart cards and similar devices Appendix 1, Version 2.0, January 2012.
- Joint Interpretation Library The Application of CC to Integrated Circuits, Version 3.0, February 2009.
- Joint Interpretation Library Security requirements for post-delivery code loading, Version 1.0, February 2016.
- Validity of conducted tests on Security Smart Card ICs in dependence of test date,
   Version 1, 2017-03-15, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 26,
   Evaluationsmethodologie für in Hardware Integrierte Schaltungen, Version 10, 2017-07-03,
   Bundesamt für Sicherheit in der Informationstechnik.
- Auswahl geeigneter Chips für DPA-Messungen, Version 1.1, 2008-12-07, Bundesamt für Sicherheit in der Informationstechnik.
- Special Attack Methods for Smartcards and Similar Devices, Version 1.4, 2011-06-08, Bundesamt für Sicherheit in der Informationstechnik.
- CC Supporting Document Mandatory Technical Document Requirements to perform Integrated Circuit Evaluations, Version 1.1, May 2013, CCDB-2013-05-001.
- Joint Interpretation Library Application of Attack Potential to Smartcards, Version 3.2, 2022-11.
- Joint Interpretation Library Attack Methods for Smartcards and Similar Devices, Version 2.4, 2020-01, confidential.
- Joint Interpretation Library Requirements to perform Integrated Circuit Evaluations, Version 1.1, February 2013.
- Application Notes and Interpretation of the Scheme (AIS) AIS 27, Transition from ITSEC to CC, Version 5, 2010-08-17, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 31,
   Funktionalitätsklassen und Evaluationsmethodologie für physikalische
   Zufallszahlengeneratoren, Version 3, 2013-05-15, Bundesamt für Sicherheit in der Informationstechnik.

 Developer evidence for the evaluation of a physical true random generator, Version 0.8, 2013-02-28, Bundesamt für Sicherheit in der Informationstechnik.

- Evaluation Report as part of the Evaluation Technical Report, Part B ETR-Part True Physical and Hybrid Random Number Generator, Template-Version 0.7, 2013-02-28, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 32, CC-Interpretationen im deutschen Zertifizierungsschema, Version 7, 2011-06-08, Bundesamt für Sicherheit in der Informationstechnik.
- Application Notes and Interpretation of the Scheme (AIS) AIS 34, Evaluation Methodology for CC Assurance Classes for EAL5+ (CC v2.3 & v3.1) and EAL6 (CC v3.1), Version 3, 2009-09-03, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 35, Öffentliche Fassung eines Security Target (ST-Lite), Version 2, 2007-11-12, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 36,
   Kompositionsevaluierung, Version 5, 2017-03-15, Bundesamt für Sicherheit in der Informationstechnik.
- CC Supporting Document Mandatory Technical Document Composite product evaluation for Smart Cards and similar devices, Version 1.4, December 2015, CCDB-2015-12-001.
- Joint Interpretation Library Composite product evaluation for Smart Cards and similar devices, Version 1.5.1, May 2018.
- CC Supporting Document Guidance ETR template for composite evaluation of Smart Cards and similar devices, Version 1.1, December 2015, CCDB-2015-12-002.
- Joint Interpretation Library ETR template for composite evaluation of Smart Cards and similar devices, Version 1.1, August 2015.
- Joint Interpretation Library Certification of "open" smart card products, Version 1.1 (for trial use), 2013-02-04.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 37, Terminologie und Vorbereitung von Smartcard-Evaluierungen, Version 3, 2010-05-17, Bundesamt für Sicherheit in der Informationstechnik.
- CC Supporting Document Guidance Smartcard Evaluation, Version 2.0, February 2010. CCDB-2010-03-001.
- Application Notes and Interpretation of the Scheme (AIS) AIS 38, Reuse of evaluation results, Version 2, 2007-09-28, Bundesamt für Sicherheit in der Informationstechnik.
- Application Notes and Interpretation of the Scheme (AIS) AIS 41, Guidelines for PPs and STs, Version 2, 2011-01-31, Bundesamt für Sicherheit in der Informationstechnik.
- Guidance Document The PP/ST Guide, Version 2, Revision 0, 2010-08, Bundesamt für Sicherheit in der Informationstechnik.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 46, Informationen zur Evaluierung von kryptographischen Algorithmen und ergänzende Hinweise für die Evaluierung von Zufallszahlengeneratoren, Version 3, 2013-12-04, Bundesamt für Sicherheit in der Informationstechnik.

 Review-Protokoll zum (Krypto-)AVA-KickOff, Template-Version/Date: 2019-08-23, Bundesamt für Sicherheit in der Informationstechnik.

- Minimal Requirements for Evaluating Side-Channel Attack Resistance of Elliptic Curve Implementations, Version 1.0.4, 2011-07-01, BSI.
- Methodology for cryptographic rating of memory encryption schemes used in smartcards and similar devices, Version 1.0, 2013-10-31, BSI.
- Minimum Requirements for Evaluating Side-Channel Attack Resistance of RSA, DSA and Diffie-Hellman Key Exchange Implementations, Version 1.0, 2013-01-14, BSI.
- Anwendungshinweise und Interpretationen zum Schema (AIS) AIS 47, Regelungen zu Site Certification, Version 1.1, 2013-12-04, Bundesamt für Sicherheit in der Informationstechnik.
- Guidance for Site Certification, Version 1.1, 2013-12-04, Bundesamt für Sicherheit in der Informationstechnik.
- Joint Interpretation Library Minimum Site Security Requirements, Version 3.0, 02/2020. (see [4] for respective AIS references).

For RNG assessment the scheme interpretations AIS20/31 was used (see [4]).

To support composite evaluations according to AIS 36 the document ETR for composite evaluation [10] was provided and approved. This document provides details of this platform evaluation that have to be considered in the course of a composite evaluation on top.

The assurance refinements outlined in the Security Target were followed in the course of the evaluation of the TOE.

As a result of the evaluation the verdict PASS is confirmed for the following assurance components:

- All components of the EAL 6 package including the class ASE as defined in the CC (see also part C of this report)
- The components ALC\_FLR.1 augmented for this TOE evaluation.

As the evaluation work performed for this certification procedure was carried out as a reevaluation based on the certificate BSI-DSZ-CC-1107-V4-2023, re-use of specific evaluation tasks was possible.

The evaluation has confirmed:

- PP Conformance: Security IC Platform Protection Profile with Augmentation Packages Version 1.0, 13 January 2014, BSI-CC-PP-0084-2014 [8]
- for the Functionality: PP conformant plus product specific extensions
   Common Criteria Part 2 extended
- for the Assurance: Common Criteria Part 3 conformant EAL 6 augmented by ALC FLR.1

For specific evaluation results regarding the development and production environment see annex B in part D of this report.

The results of the evaluation are only applicable to the TOE as defined in chapter 2 and the configuration as outlined in chapter 8 above.

## 9.2. Results of cryptographic assessment

The strength of the cryptographic algorithms was not rated in the course of this certification procedure (see BSIG Section 9, Para. 4, Clause 2). But cryptographic functionalities with a security level of lower than 120 bits can no longer be regarded as secure without considering the application context. Therefore, for these functionalities it shall be checked whether the related crypto operations are appropriate for the intended system. Some further hints and guidelines can be derived from the 'Technische Richtlinie BSI TR-02102' (https://www.bsi.bund.de).

The following table gives an overview of the cryptographic functionalities inside the TOE to enforce the security policy and outlines its rating from cryptographic point of view. Any Cryptographic Functionality that is marked in column 'Security Level above 120 Bits' of the following table with 'no' achieves a security level of lower than 120 Bits (in general context) only. As a transition policy the usage of RSA-based signatures with key sizes above 2000 bits is conform to the TR-02102 within the year 2023.

| No. | Purpose                 | Cryptographic<br>Mechanism                         | Standard of<br>Implementation     | Key Size<br> k  in<br>Bits | Comments | Security<br>Level<br>above 120<br>Bits |
|-----|-------------------------|--|-----------------------------------|----------------------------|----------|--|
| Sym | metric Coproces         | sor (SCP)  |                                   |                            |          |  |
| 1   | Cryptographic primitive | TDES   | [NIST SP800-67],<br>[ISO_18033-3] | 112, 168                   | -        | -                                      |
| 2   | Cryptographic primitive | AES  | [FIPS197],<br>[ISO_18033-3]       | 128, 192,<br>256           | -        | -                                      |
| 3   | Confidentiality         | #1 in ECB mode<br>for encryption<br>and decryption | [NIST SP800-38A]                  | 112, 168                   | -        | No                                     |
| 4   | Confidentiality         | #1 in CBC mode<br>for encryption<br>and decryption | [NIST SP800-38A]                  | 112, 168                   | -        | No                                     |
| 5   | Confidentiality         | #2 in ECB mode<br>for encryption<br>and decryption | [NIST SP800-38A]                  | 128, 192,<br>256           | -        | No                                     |
| 6   | Confidentiality         | #2 in CBC mode<br>for encryption<br>and decryption | [NIST SP800-38A]                  | 128, 192,<br>256           | -        | Yes                                    |
| Sym | metric Cryptogra        | phic Libraries (bot                                | h SCLs)                           |                            |          |  |
| 7   | Cryptographic primitive | TDES   | [NIST SP800-67]                   | 112, 168                   | -        | <u>-</u>                               |
| 8   | Cryptographic primitive | AES  | [FIPS197]                         | 128, 192,<br>256           | -        | -                                      |
| 9   | Confidentiality         | #7 in ECB mode for encryption                      | [NIST SP800-38A]                  | 112, 168                   | -        | No                                     |

| No.  | Purpose                 | Cryptographic<br>Mechanism                         | Standard of<br>Implementation                           | Key Size<br> k  in<br>Bits | Comments | Security<br>Level<br>above 120<br>Bits |
|------|-------------------------|--|---|----------------------------|----------|--|
|      |                         | and decryption                                     |   |                            |          |  |
| 10   | Confidentiality         | #7 in CBC mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 112, 168                   | -        | No                                     |
| 11   | Confidentiality         | #7 in CTR mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 112, 168                   | -        | No                                     |
| 12   | Confidentiality         | #7 in CFB mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 112, 168                   | -        | No                                     |
| 13   | Integrity<br>protection | #7 in CMAC mode for MAC generation                 | [NIST SP800-38B]  | 112, 168                   | -        | No                                     |
| 14   | Integrity<br>protection | #7 in Retail MAC (Algorithm 3) for MAC generation  | [ISO9797-1]   | 112                        | -        | No                                     |
| 15   | Confidentiality         | #8 in ECB mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 128, 192,<br>256           | -        | No                                     |
| 16   | Confidentiality         | #8 in CBC mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 128, 192,<br>256           | -        | Yes                                    |
| 17   | Confidentiality         | #8 in CTR mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 128, 192,<br>256           | -        | Yes                                    |
| 18   | Confidentiality         | #8 in CFB mode<br>for encryption<br>and decryption | [NIST SP800-38A]  | 128, 192,<br>256           | -        | Yes                                    |
| 19   | Integrity<br>protection | #8 in CMAC mode for MAC generation                 | [NIST SP800-38B]  | 128, 192,<br>256           | -        | No                                     |
| Asyr | nmetric Cryptogr        | aphic Library (ACL                                 | .) v3.02.000  |                            |          |  |
| 20   | Confidentiality         | encryption   | 1 -   | 1024 –<br>2112             | -        | No                                     |
| 21   | Confidentiality         | decryption   | [PKCS #1, 5.1.2],<br>[IEEE_P1363, 8.2.1<br>(I) / 8.2.3] |                            | -        | No                                     |
| 22   | Confidentiality         | decryption with CRT                                | [PKCS #1, 5.1.2],<br>[IEEE_P1363, 8.2.1                 |                            | -        | Yes for key size >=                    |

| No. | Purpose        | Cryptographic<br>Mechanism  | Standard of<br>Implementation                            | Key Size<br> k  in<br>Bits | Comments   | Security<br>Level<br>above 120<br>Bits                     |
|-----|----------------|---|--|----------------------------|--|--|
| 23  | Authenticity   | signature   | (II) / 8.2.3]<br>[PKCS #1, 5.2.1],                       | 1024 –                     | -  | 2800 bit<br>For Keysize                                    |
|     |                | generation  | [IEEE_P1363, 8.2.1<br>(I) / 8.2.4]                       |                            |  | >=2000bit:<br>security<br>level<br>>=100bit                |
| 24  | Authenticity   | signature<br>generation with<br>CRT   | [PKCS #1, 5.2.1],<br>[IEEE_P1363, 8.2.1<br>(II) / 8.2.4] |                            | -  | Yes for key<br>size >=<br>2800 bit                         |
| 25  | Authenticity   | signature<br>verification   | [PKCS #1, 5.2.2],<br>[IEEE_P1363, 8.2.5]                 | 1024 –<br>4224             | -  | Yes for key<br>size >=<br>2800 bit                         |
| 26  | Key generation | RSA key generation returning CRT key components dp, dq and qinv (prime generation not included) | [PKCS #1, 3.1 / 3.2],<br>[IEEE_P1363,<br>8.1.3.1]        | 1024 –<br>4224             | Method CRT   | Yes for key<br>size >=<br>2800 bit                         |
| 27  | Key generation | RSA key generation returning key representation n and d (prime generation not included)         | [PKCS #1, 3.1 / 3.2],<br>[IEEE_P1363,<br>8.1.3.1]        | 1024 –<br>2112             | Method n_d   | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 28  | Key generation | RSA key generation returning key representation p, q and d (prime generation included)          | [IEEE_P1363,<br>8.1.3.1]                                 | 1024 –<br>2047             | Method p_q_d; Prime generation method follows [FIPS186-4, B.3.3] but due to key size considered proprietary. | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 29  | Key generation | RSA key generation returning key representation p, q and d (prime generation included)          | [IEEE_P1363,<br>8.1.3.1]<br>[FIPS186-4, B.3.3]           | 2048 –<br>2112             | Method p_q_d   | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 30  | N/A            | Supported elliptic curves: - All curves in  | [FIPS186-4]<br>[RFC5639]                                 | N/A                        | _  | -  |

| No.  | Purpose                               | Cryptographic<br>Mechanism                                       | Standard of<br>Implementation                                   | Key Size<br> k  in<br>Bits | Comments  | Security<br>Level<br>above 120<br>Bits                                      |
|------|---------------------------------------|--|---|----------------------------|---|---|
|      |                                       | [FIPS186-4],<br>- All curves in<br>[RFC5639].                    |   |                            |   |   |
| 31   | Part of<br>Cryptographic<br>primitive | EC point addition on curves listed in #30                        | N/A   | 160 –<br>521               | -   | Not<br>applicable   |
| 32   | Authenticity                          | ECDSA<br>signature<br>generation on<br>curves listed in<br>#30   | [ANS X9.62, 7.3],<br>[IEEE_P1363, 7.2.7]                        | 160 –<br>521               | hash calculation of ECDSA is not implemented by the library and lies in the responsibility of the user. | No for key<br>size<br>160,163,19<br>2, 224<br>Yes for key<br>sizes<br>>=250 |
| 33   | Authenticity                          | ECDSA<br>signature<br>verification on<br>curves listed in<br>#30 | [ANS X9.62, 7.4.1]<br>[IEEE_P1363, 7.2.8]                       | 160 –<br>521               | hash calculation of ECDSA is not implemented by the library and lies in the responsibility of the user. | No for key<br>size<br>160,163,19<br>2, 224<br>Yes for key<br>sizes<br>>=250 |
| 34   | Key agreement                         | Diffie-Hellman<br>(ECDH) key                                     | [ANS X9.63, 5.4.1]<br>[ISO_11770-3, D.6]<br>[IEEE_P1363, 7.2.1] | 160 –<br>521               | _   | No for key<br>size<br>160,163,19<br>2, 224<br>Yes for key<br>sizes<br>>=250 |
| 35   | Key generation                        | Elliptic Curve<br>key generation<br>on curves listed<br>in #30   | [ANS X9.62, A.4.3]<br>[IEEE_P1363,<br>A.16.9]                   | 160 –<br>521               | _   | No for key<br>size<br>160,163,19<br>2, 224<br>Yes for key<br>sizes<br>>=250 |
| Asyr | nmetric Cryptogr                      | aphic Libraries (A0  | CLs) v3.33.003, v3.34.0   | 000 and 3.3                | 35.001  |   |
| 36   | Confidentiality                       | RSA encryption   | [PKCS #1, 5.1.1]  | 1024 –                     | _   | Yes for key   |

| No. | Purpose         | Cryptographic<br>Mechanism  | Standard of<br>Implementation                           | Key S<br> k <br>Bits | Size<br>in | Comments   | Security<br>Level<br>above 120<br>Bits                     |
|-----|-----------------|---|---|----------------------|------------|--|--|
|     |                 |   | [IEEE_P1363, 8.2.2]                                     | 4224                 |            |  | size >=<br>2800 bit  |
| 37  | Confidentiality | RSA decryption  | [PKCS #1, 5.1.2]<br>[IEEE_P1363, 8.2.1<br>(I) / 8.2.3]  | 1024<br>2112         | -          | _  | Yes for key<br>size >=<br>2800 bit                         |
| 38  | Confidentiality | RSA decryption with CRT   | [PKCS #1, 5.1.2]<br>[IEEE_P1363, 8.2.1<br>(II) / 8.2.3] | 1024<br>4224         | _          | _  | Yes for key<br>size >=<br>2800 bit                         |
| 39  | Authenticity    | RSA signature generation  | [PKCS #1, 5.2.1]<br>[IEEE_P1363, 8.2.1<br>(I) / 8.2.4]  | 1024<br>2112         |            | _  | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 40  | Authenticity    | RSA signature<br>generation with<br>CRT   | [PKCS #1, 5.2.1]<br>[IEEE_P1363, 8.2.1<br>(II) / 8.2.4] | 1024<br>4224         | -          | -  | Yes for key<br>size >=<br>2800 bit                         |
| 41  | Authenticity    | RSA signature verification  | [PKCS #1, 5.2.2]<br>[IEEE_P1363, 8.2.5]                 | 1024<br>4224         | _          | _  | Yes for key<br>size >=<br>2800 bit                         |
| 42  | Key generation  | RSA key generation returning CRT key components dp, dq and qinv (prime generation not included) | [PKCS #1, 3.1 / 3.2]<br>[IEEE_P1363,<br>8.1.3.1]        | 1024<br>4224         |            | Method CRT   | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 43  | Key generation  | RSA key generation returning key representation n and d (prime generation not included)         | [PKCS #1, 3.1 / 3.2]<br>[IEEE_P1363,<br>8.1.3.1]        | 1024<br>2112         | I          | Method n_d   | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 44  | Key generation  | RSA key generation returning key representation p, q and d (prime generation included)          | [IEEE_P1363,<br>8.1.3.1]                                | 1024<br>2047         | _          | Method p_q_d;<br>Prime generation<br>method follows<br>[FIPS186-4, B.3.3]<br>but due to key size<br>considered<br>proprietary. | For Keysize<br>>=2000bit:<br>security<br>level<br>>=100bit |
| 45  | Key generation  | RSA key<br>generation   | [IEEE_P1363,<br>8.1.3.1]                                | 2048<br>2112         | -          | Method p_q_d   | For Keysize<br>>=2000bit:                                  |

| No. | Purpose  | Cryptographic<br>Mechanism   | Standard of<br>Implementation  | Key Size<br> k  in<br>Bits                | Comments   | Security<br>Level<br>above 120<br>Bits |
|-----|--|--|--|---|--|--|
|     |  | returning key<br>representation<br>p, q and d<br>(prime<br>generation<br>included) | [FIPS186-4, B.3.3]   |   |  | security<br>level<br>>=100bit          |
| 46  | Supporting Function for Cryptographic primitive (available only for ACL v3.35.001) | Prime number generation  | _  | length of<br>prime:<br>512 –<br>2112 Bits | Method PRIME_GEN; Proprietary prime number generation method, which follows [PrimeGen] | Not<br>applicable                      |
| 47  | Supporting<br>Function for<br>Cryptographic<br>primitive                           |  | [FIPS186-4, B.3.3 /<br>C.3.1]  | length of<br>prime:<br>512 –<br>2064 Bits | Method<br>2PRIME_GEN   | Not<br>applicable                      |
| 48  | Supporting<br>Function for<br>Cryptographic<br>primitive                           | Primality test   | _  | length of<br>prime:<br>512 –<br>2112 Bits | Method<br>PRIME_CHECK;<br>Proprietary<br>primality test                                | Not<br>applicable                      |
| 49  | Supporting<br>Function for<br>Cryptographic<br>primitive                           | Primality test   | [FIPS186-4, C.3.1 /<br>C.3.2]  | length of<br>prime:<br>512 –<br>2064 Bits | Method<br>PRIME_CHECK_<br>MASK   | Not<br>applicable                      |
| 50  | Key agreement  | RSA Diffie-<br>Hellman (DH)<br>key agreement                                       | [N186-4, B.5.5]<br>[RSA-PKCSB,<br>5.2.1 / 5.1.2]<br>[IEEE1336, 8.2.4 /<br>8.2.3] | 1024 –<br>4224                            | Method RSA_DH  | Yes for key<br>size >=<br>2800 bit     |
| 51  | N/A  | Supported elliptic curves: - All curves in [FIPS186-4], - All curves in [RFC5639]. | [FIPS186-4],<br>[RFC5639]  | N/A                                       | _  | N/A                                    |
| 52  | Supporting<br>Function for<br>Cryptographic<br>primitive                           | EC point addition on curves listed in #51  | N/A  | 160 –<br>521                              | _  | Not<br>applicable                      |
| 53  | Authenticity   | ECDSA<br>signature<br>generation on<br>curves listed in                            | [ANS X9.62, 7.3]<br>[IEEE_P1363, 7.2.7]  | 160 –<br>521                              | hash calculation of<br>ECDSA is not<br>implemented by<br>the library and lies          | No for key<br>size<br>160,163,19       |

| No.  | Purpose                       | Cryptographic<br>Mechanism                                  | Standard of<br>Implementation             | Key<br> k <br>Bits | Size<br>in | Comments  | Security<br>Level<br>above 120<br>Bits |
|------|-------------------------------|---|---|--------------------|------------|---|--|
|      |                               | #51   |   |                    |            | in the responsibility of the user.                    | 2, 224                                 |
|      |                               |   |   |                    |            | and deen.   | Yes for key<br>sizes<br>>=250          |
| 54   | Authenticity                  | ECDSA<br>signature<br>verification on                       | [ANS X9.62, 7.4.1]<br>[IEEE_P1363, 7.2.8] | 160<br>521         | _          | hash calculation of<br>ECDSA is not<br>implemented by | size                                   |
|      |                               | curves listed in<br>#51                                     |   |                    |            | the library and lies<br>in the<br>responsibility of   | 160,163,19<br>2, 224                   |
|      |                               |   |   |                    |            | the user.   | Yes for key<br>sizes<br>>=250          |
| 55   | Key agreement                 | Diffie-Hellman  | [ANS X9.63, 5.4.1]<br>[ISO_11770-3, D.6]  | 160<br>521         | _          | _   | No for key<br>size                     |
|      |                               |   | [IEEE_P1363, 7.2.1]                       |                    |            |   | 160,163,19<br>2, 224                   |
|      |                               |   |   |                    |            |   | Yes for key<br>sizes<br>>=250          |
| 56   | Key generation                | Elliptic Curve<br>key generation<br>on curves listed        | [ANS X9.62, A.4.3]<br>[IEEE_P1363,        | 160<br>521         | _          | _   | No for key<br>size                     |
|      |                               | in #51  | A.16.9]                                   |                    |            |   | 160,163,19<br>2, 224                   |
|      |                               |   |   |                    |            |   | Yes for key<br>sizes<br>>=250          |
| 57   | PACE<br>integrated<br>mapping | Point encoding<br>for the ECDH-<br>integrated<br>mapping on | [ICAO_11, B.2]                            | 160<br>521         | _          | _   | Not<br>applicable                      |
|      |                               | curves listed in<br>#51                                     |   |                    |            |   |  |
| Flas | n Loader                      |   |   |                    |            |   |  |
| 58   | Confidentiality               | #2 in CCM<br>mode for<br>encryption and<br>decryption       | [NIST SP800-38C]                          | 128                |            | _   | Not rated                              |
| 59   | Authenticity                  | #2 in CCM<br>mode for MAC                                   | [NIST SP800-38C]                          | 128                |            | _   | Not rated                              |

| No.                                 | Purpose             | Cryptographic<br>Mechanism                            | Standard of<br>Implementation                  | Key Size<br> k  in<br>Bits | Comments  | Security<br>Level<br>above 120<br>Bits |
|-------------------------------------|---------------------|---|--|----------------------------|---|--|
|                                     |                     | verification  |  |                            |   |  |
| 60                                  | Authentication      | Mutual<br>authentication<br>protocol based<br>on #59  | [AGD_PPUM, 2.1.5]<br>/ [AGD_PPUM_FU,<br>2.1.8] | 128                        | -   | Not rated                              |
| 61                                  | Authentication      | External<br>authentication<br>protocol based<br>on #5 | [AGD_PPUM, 2.1.5]<br>/ [AGD_PPUM_FU,<br>2.1.8] | 128                        | _   | Not rated                              |
| Ran                                 | dom Number ger      | neration (Hardware                                    | •)   |                            |   |  |
| 62                                  | RNG                 | Physical RNG  | PTG.2 in [AIS31]                               | N/A                        | _   | Not<br>applicable                      |
| 63                                  | RNG                 | Hybrid RNG  | corresponds to<br>PTG.3 in [AIS31]             | N/A                        | _   | Not<br>applicable                      |
| 64                                  | RNG                 | Deterministic<br>RNG                                  | corresponds to DRG.3 in [AIS20]                | N/A                        | _   | Not<br>applicable                      |
| 65                                  | RNG                 | Deterministic<br>RNG                                  | corresponds to<br>DRG.4 in [AIS20]             | N/A                        | _   | Not<br>applicable                      |
| Ran                                 | dom Crypto Libra    | ary (RCL) v1.10.00                                    | 7  |                            |   |  |
| 66                                  | RNG                 | Physical RNG  | PTG.2 in [AIS31]                               | N/A                        | The RCL acts as interface to the PTG.2 hardware RNG | Not<br>applicable                      |
| 67                                  | RNG                 | Deterministic<br>RNG                                  | corresponds to DRG.3 in [AIS20]                | 128, 256                   | CTR_DRBG  | Not<br>applicable                      |
|                                     |                     |   | [NIST SP800-90A]                               |                            |   |  |
| 68                                  | RNG                 | Deterministic<br>RNG                                  | corresponds to DRG.4 in [AIS20]                | 128, 256                   | CTR_DRBG  | Not<br>applicable                      |
|                                     |                     |   | [NIST SP800-90A]                               |                            |   |  |
| Hash Crypto Library (HCL) v1.13.002 |                     |   |  |                            |   |  |
| 69                                  | Hash<br>calculation | SHA-1   | [FIPS180-4]                                    | N/A                        | _   | Not<br>applicable                      |
| 70                                  | Hash<br>calculation | SHA-224   | [FIPS180-4]                                    | N/A                        | _   | Not<br>applicable                      |
| 71                                  | Hash<br>calculation | SHA-256   | [FIPS180-4]                                    | N/A                        | _   | Not<br>applicable                      |
| 72                                  | Hash                | SHA-384   | [FIPS180-4]                                    | N/A                        | _   | Not                                    |

| No. | Purpose             | Cryptographic<br>Mechanism | Standard of<br>Implementation | Key Size<br> k  in<br>Bits | Comments | Security<br>Level<br>above 120<br>Bits |
|-----|---------------------|----------------------------|-------------------------------|----------------------------|----------|--|
|     | calculation         |                            |                               |                            |          | applicable                             |
| 73  | Hash<br>calculation | SHA-512                    | [FIPS180-4]                   | N/A                        | _        | Not<br>applicable                      |
| 74  | Hash<br>calculation | SHA-512/224                | [FIPS180-4]                   | N/A                        | _        | Not<br>applicable                      |
| 75  | Hash<br>calculation | SHA-512/256                | [FIPS180-4]                   | N/A                        | _        | Not<br>applicable                      |

Table 3: TOE cryptographic functionality

The TOE's memory enryption, named ICS ("ICS-C8") and not separately listed above, was successfully evaluated according to BSI's "Methodology for cryptographic rating of memory encryption schemes used in smartcards and similar devices" (Version 1.0, 2013-10-31).

Further conformance evaluation and assessment to claimed cryptographic functionality standards is documented in the confidential report "Cryptographic Standards Compliance Verification" [25].

Reference of Legislatives and Standards quoted above:

(NIST)

| [AIS20]     | Anwendungshinweise und Interpretationen zum Schema (AIS) – AIS 20, Funktionalitätsklassen und Evaluationsmethodologie für deterministische Zufallszahlengeneratoren, Version 3, 2013-05-15, Bundesamt für Sicherheit in der Informationstechnik         |  |
|-------------|---|--|
| [AIS31]     | Anwendungshinweise und Interpretationen zum Schema (AIS) – AIS 31, Funktionalitätsklassen und Evaluationsmethodologie für physikalische Zufallszahlengeneratoren, Version 3, 2013-05-15, Bundesamt für Sicherheit in der Informationstechnik            |  |
| [ANS X9.62] | American National Standard for Financial Services ANS X9.62-2005, Public Key Cryptography for the Financial Services Industry, The Elliptic Curve Digital Signature Algorithm (ECDSA), November 16, 2005, American National Standards Institute.        |  |
| [ANS X9.63] | American National Standard for Financial Services X9.63-2011, Public Key Cryptography for the Financial Services Industry - Key Agreement and Key Transport Using Elliptic Curve Cryptography, December 21, 2011, American National Standards Institute |  |
| [AGD_PPUM]  | see reference [15] in bibliography (section 14)   |  |
| [FIPS186-4] | Federal Information Processing Standards Publication FIPS PUB 186-4, Digital Signature Standard (DSS), July 2013, U.S. department of Commerce / National Institute of Standards and Technology  |  |

| [FIPS197]        | Federal Information Processing Standards Publication 197,<br>Announcing the ADVANCED ENCRYPTION STANDARD (AES),<br>2001-11-26, National Institute of Standards and Technology (NIST)  |
|------------------|---|
| [IEEE_P1363]     | IEEE P1363. Standard specifications for public key cryptography. IEEE, 2000   |
| [ISO_9797-1]     | Information technology - Security techniques - Message Authentication Codes (MACs) - Part 1: Mechanisms using a block cipher, 1999-12, ISO/IEC  |
| [ISO_11770-3]    | ISO 11770-3: Information technology - Security techniques - Key management Part 3: Mechanisms using asymmetric techniques, ISO/IEC 11770-3:2008   |
| [ISO_18033-3]    | ISO 18033-3: Information technology - Security techniques - Encryption algorithms - Part 3: Block ciphers, ISO/IEC 18033-3:2005   |
| [NIST SP800-38A] | NIST SP800-38A, Recommendation for Block Cipher Modes of Operation, Methods and Techniques, 2001, National Institute of Standards and Technology (NIST)   |
| [NIST SP800-38B] | NIST SP800-38B, Recommendation for Block Cipher Modes of Operation, The CMAC Mode for Authentication, 2005-05, National Institute of Standards and Technology (NIST)  |
| [NIST SP800-38C] | NIST SP800-38C, Recommendation for Block Cipher Modes of Operation: the CCM Mode for Authentication and Confidentiality, 2004-05 with updates as of 2007-07-20, National Institute of Standards and Technology (NIST)   |
| [NIST SP800-67]  | NIST Special Publication 800-67 – Revision 2, Recommendation for<br>the Triple Data Encryption Algorithm (TDEA) Block Cipher – Revised<br>November 2017, National Institute of Standards and Technology<br>(NIST), Technology Administration, U.S. Department of Commerce |
| [PKCS-1]         | PKCS #1: RSA Cryptography Standard, Version 2.2, October 27, 2012, RSA Laboratories   |
| [RFC5639]        | RFC 5639 - Elliptic Curve Cryptography (ECC) Brainpool Standard Curves and Curve Generation, IETF Trust and the persons identified as the document authors, March 2010 (http://www.ietf.org/rfc/rfc5639.txt)  |

## 10. Obligations and Notes for the Usage of the TOE

The documents as outlined in table 2 contain necessary information about the usage of the TOE and all security hints therein have to be considered. In addition all aspects of Assumptions, Threats and OSPs as outlined in the Security Target not covered by the TOE itself need to be fulfilled by the operational environment of the TOE.

The customer or user of the product shall consider the results of the certification within his system risk management process. In order for the evolution of attack methods and techniques to be covered, he should define the period of time until a re-assessment of the TOE is required and thus requested from the sponsor of the certificate.

The limited validity for the usage of cryptographic algorithms as outlined in chapter 9 has to be considered by the user and his system risk management process, too.

Some security measures are partly implemented in this certified TOE, but require additional configuration or control or measures to be implemented by a product layer on top, e.g. the Embedded Software using the TOE. For this reason the TOE includes guidance documentation (see table 2) which contains obligations and guidelines for the developer of the product layer on top on how to securely use this certified TOE and which measures have to be implemented in order to fulfil the security requirements of the Security Target of the TOE. In the course of the evaluation of the composite product or system it must be examined if the required measures have been correctly and effectively implemented by the product layer on top. Additionally, the evaluation of the composite product or system must also consider the evaluation results as outlined in the document "ETR for composite evaluation" [10].

At the point in time when evaluation and certification results are reused there might be an update of the document "ETR for composite evaluation" available. Therefore, the certified products list on the BSI website has to be checked for latest information on reassessments, recertifications or maintenance result available for the product.

#### Furthermore:

The TOE is delivered to the composite product manufacturer and to the security IC embedded software developer. The actual end-consumer obtains the TOE from the composite product issuer together with the application which runs on the TOE.

The security IC embedded software developer receives all necessary recommendations and hints to develop his software in form of the delivered documentation.

 All security hints described in the delivered documents in [12] – [14], [16] - [28] have to be considered.

The composite product manufacturer receives all necessary recommendations and hints to develop his software in form of the delivered documentation.

All security hints described in [15] and [26] have to be considered.

## 11. Security Target

For the purpose of publishing, the Security Target [9] of the Target of Evaluation (TOE) is provided within a separate document as Annex A of this report. It is a sanitised version of the complete Security Target [6] used for the evaluation performed. Sanitisation was performed according to the rules as outlined in the relevant CCRA policy (see AIS 35 [4]).

## 12. Regulation specific aspects (eIDAS, QES)

None.

#### 13. Definitions

#### 13.1. Acronyms

AIS Application Notes and Interpretations of the Scheme

BSI Bundesamt für Sicherheit in der Informationstechnik / Federal Office for Information Security, Bonn, Germany

**BSIG** BSI-Gesetz / Act on the Federal Office for Information Security

CCRA Common Criteria Recognition ArrangementCC Common Criteria for IT Security Evaluation

**CEM** Common Methodology for Information Technology Security Evaluation

**CPP** Collaborative Protection Profile **EAL** Evaluation Assurance Level

ETR Evaluation Technical Report

IT Information Technology

ITSEF Information Technology Security Evaluation Facility

**PP** Protection Profile

**SAR** Security Assurance Requirement

**SFP** Security Function Policy

**SFR** Security Functional Requirement

**ST** Security Target

**TOE** Target of Evaluation

TSF TOE Security Functionality

#### 13.2. Glossary

**Augmentation** - The addition of one or more requirement(s) to a package.

**Collaborative Protection Profile -** A Protection Profile collaboratively developed by an International Technical Community endorsed by the Management Committee.

**Extension** - The addition to an ST or PP of functional requirements not contained in CC part 2 and/or assurance requirements not contained in CC part 3.

**Formal** - Expressed in a restricted syntax language with defined semantics based on well-established mathematical concepts.

**Informal** - Expressed in natural language.

**Object** - A passive entity in the TOE, that contains or receives information, and upon which subjects perform operations.

Package - named set of either security functional or security assurance requirements

**Protection Profile** - A formal document defined in CC, expressing an implementation independent set of security requirements for a category of IT Products that meet specific consumer needs.

**Security Target** - An implementation-dependent statement of security needs for a specific identified TOE.

**Semiformal** - Expressed in a restricted syntax language with defined semantics.

**Subject** - An active entity in the TOE that performs operations on objects.

**Target of Evaluation** - An IT Product and its associated administrator and user guidance documentation that is the subject of an Evaluation.

**TOE Security Functionality** - Combined functionality of all hardware, software, and firmware of a TOE that must be relied upon for the correct enforcement of the SFRs.

## 14. Bibliography

- [1] Common Criteria for Information Technology Security Evaluation, Version 3.1, Part 1: Introduction and general model, Revision 5, April 2017 Part 2: Security functional components, Revision 5, April 2017 Part 3: Security assurance components, Revision 5, April 2017 <a href="https://www.commoncriteriaportal.org">https://www.commoncriteriaportal.org</a>
- [2] Common Methodology for Information Technology Security Evaluation (CEM), Evaluation Methodology, Version 3.1, Rev. 5, April 2017, <a href="https://www.commoncriteriaportal.org">https://www.commoncriteriaportal.org</a>
- [3] BSI certification: Scheme documentation describing the certification process (CC-Produkte) and Scheme documentation on requirements for the Evaluation Facility, approval and licencing (CC-Stellen), https://www.bsi.bund.de/zertifizierung
- [4] Application Notes and Interpretations of the Scheme (AIS) as relevant for the TOE<sup>6</sup> https://www.bsi.bund.de/AIS
- [5] German IT Security Certificates (BSI 7148), periodically updated list published also on the BSI Website, <a href="https://www.bsi.bund.de/zertifizierungsreporte">https://www.bsi.bund.de/zertifizierungsreporte</a>
- [6] Security Target BSI-DSZ-CC-1107-V5-2024, Version 6.5, 2024-08-20, "IFX\_CCI\_00002Dh, IFX\_CCI\_000039h, IFX\_CCI\_00003Ah, IFX\_CCI\_000044h, IFX\_CCI\_000045h, IFX\_CCI\_000046h, IFX\_CCI\_000047h, IFX\_CCI\_000048h, IFX\_CCI\_000049h, IFX\_CCI\_00004Ah, IFX\_CCI\_00004Bh, IFX\_CCI\_00004Ch, IFX\_CCI\_00004Dh, IFX\_CCI\_00004Eh T11 Security Target", Infineon Technologies AG (confidential document)
- [7] Evaluation Technical Report, Version 2, 2024-09-02, EVALUATION TECHNICAL REPORT SUMMARY (ETR SUMMARY), TÜV Informationstechnik GmbH, (confidential document)
- [8] Security IC Platform Protection Profile with Augmentation Packages Version 1.0, 13 January 2014, BSI-CC-PP-0084-2014
- [9] Security Target Lite BSI-DSZ-CC-1107-V5-2024, Version 6.5, 2024-08-20, IFX\_CCI\_00002Dh, IFX\_CCI\_000039h, IFX\_CCI\_00003Ah, IFX\_CCI\_000044h, IFX\_CCI\_000045h, IFX\_CCI\_000046h, IFX\_CCI\_000047h, IFX\_CCI\_000048h, IFX\_CCI\_000049h, IFX\_CCI\_00004Ah, IFX\_CCI\_00004Bh, IFX\_CCI\_00004Ch, IFX\_CCI\_00004Dh, IFX\_CCI\_00004Eh T11 Security Target Lite, Infineon Technologies AG. (sanitised public document)
- [10] ETR for composite evaluation according to AIS 36 for BSI-DSZ-CC-1107-V4-2023, Version 3, 2023-11-27, EVALUATION TECHNICAL REPORT FOR COMPOSITE EVALUATION (ETR COMP), TÜV Informationstechnik GmbH (confidential document)

and

Addendum to ETR for composite, Version V2, 2024-09-02, TÜV Informationstechnik GmbH (confidential document)

<sup>&</sup>lt;sup>6</sup> See section 9.1 for relevant AIS

[11] Configuration list for the TOE, Version 2.0, 2021-03-02, "Infineon Technologies AG Chipcard and Security Evaluation Documentation Life Cycle Support", Infineon Technologies AG (confidential document)

- [12] 32-bit Security Controller V11, Hardware Reference Manual, V6.2, 2020-12-21, Infineon Technologies AG
- [13] 32-bit Security Controller, SLx1/SLx3 Controller Family, Programmer's Reference Manual, V5.6, 2023-07-06 Infineon Technologies AG
- [14] 32-bit Security Controller V11, Security Guidelines, V1.00-2976, 2023-06-19, Infineon Technologies AG
- [15] Production and personalization 32-bit security controller, V09.12, 2023-03-02, Infineon Technologies AG
- [16] 32-bit Security Controller, Crypto2304T V3, User Manual (optional), V3.0, 2024-06-21, Infineon Technologies AG
- [17] HSL for SLCx7V11a Hardware Support Library (optional), V03.52.9708, 2021-01-25, Infineon Technologies AG
- [18] UMSLC library for SLCx7 in 40nm, User Mode Security Life Control, V01.30.0564, 2019-06-19, Infineon Technologies AG
- [19] SCL37-SCP-v440-C40, Symmetric Crypto Library for SCP-v440 AES/DES/MAC, 32-bit Security Controller, User interface manual (optional) V2.11.003, 2021-06-16, Infineon Technologies AG
- [20] SCL37-SCP-v440-C40, Symmetric Crypto Library for SCP-v440 AES/DES/MAC, 32-bit Security Controller, User interface manual (optional) V2.15.000, 2023-07-20, Infineon Technologies AG
- [21] ACL37-Crypto2304T-C40, Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox, 32-bit Security Controller, User interface manual (optional), V3.02.000, 2024-08-16, Infineon Technologies AG
- [22] ACL37-Crypto2304T-C40, Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox, 32-bit Security Controller, User interface manual (optional), V3.33.003, 2024-08-16, Infineon Technologies AG
- [23] RCL37-X-C40 Random Crypto Library for SCP-v440 & RNG-v3 DRBG/HWRNG 32-bit Security Controller, User interface manual (optional), V1.10.007, 2020-06-16, Infineon Technologies AG
- [24] HCL37-CPU-C40 Hash Crypto Library for CPU SHA 32-bit Security Controller, User interface manual (optional), V1.13.002,2020-05-07, Infineon Technologies AG
- [25] "Cryptographic Standards Compliance Verification", Version 2, 2024-08-23, TÜV Informationstechnik GmbH (confidential document)
- [26] SLx3 (40 nm) Security Controllers Production and Personalization Manual Flash Loader V9 Field update, V09.14, 2023-07-21, Infineon Technologies AG
- [27] ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox 32-bit Security Controller User interface manual (optional), V3.34.000, 2024-08-16, Infineon Technologies AG

[28] ACL37-Crypto2304T-C40 Asymmetric Crypto Library for Crypto2304T RSA/ECC/Toolbox 32-bit Security Controller User interface manual (optional), V3.35.001, 2024-06-06, Infineon Technologies AG

## C. Excerpts from the Criteria

For the meaning of the assurance components and levels the following references to the Common Criteria can be followed:

- On conformance claim definitions and descriptions refer to CC part 1 chapter 10.5
- On the concept of assurance classes, families and components refer to CC Part 3 chapter 7.1
- On the concept and definition of pre-defined assurance packages (EAL) refer to CC Part 3 chapters 7.2 and 8
- On the assurance class ASE for Security Target evaluation refer to CC Part 3 chapter 12
- On the detailed definitions of the assurance components for the TOE evaluation refer to CC Part 3 chapters 13 to 17
- The table in CC part 3 , Annex E summarizes the relationship between the evaluation assurance levels (EAL) and the assurance classes, families and components.

The CC are published at https://www.commoncriteriaportal.org/cc/

#### D. Annexes

## List of annexes of this certification report

Annex A: Security Target provided within a separate document.

Annex B: Evaluation results regarding development

and production environment

## Annex B of Certification Report BSI-DSZ-CC-1107-V5-2024

# **Evaluation results regarding development and production environment**



The IT product IFX\_CCI\_00002Dh, 000039h, 00003Ah, 000044h, 000045h, 000046h, 000047h, 000048h, 000049h, 00004Ah, 00004Bh, 00004Ch, 00004Dh, 00004Eh design step T11 with firmware 80.306.16.0, 80.306.16.1 or 80.312.02.0, optional NRG™ SW 05.03.4097, optional HSL v3.52.9708, UMSLC lib v01.30.0564, optional SCL v2.15.000 or v2.11.003, optional ACL v3.35.001, v3.34.000, v3.33.003 or v3.02.000, optional RCL v1.10.007, optional HCL v1.13.002 and user guidance (Target of Evaluation, TOE) has been evaluated at an approved evaluation facility using the Common Methodology for IT Security Evaluation (CEM), Version 3.1 extended by Scheme Interpretations, by advice of the Certification Body for components beyond EAL 5 and CC Supporting Documents for conformance to the Common Criteria for IT Security Evaluation (CC), Version 3.1.

As a result of the TOE certification, dated 4 September 2024, the following results regarding the development and production environment apply. The Common Criteria assurance requirements ALC – Life cycle support (i.e. ALC\_CMC.5, ALC\_CMS.5, ALC\_DEL.1, ALC\_DVS.2, ALC\_FLR.1, ALC\_LCD.1, ALC\_TAT.3) are fulfilled for the development and production sites of the TOE listed below in Table 4.

| Distribution Center name | Address   |
|--------------------------|---|
| DHL Singapore            | DHL Exel Supply Chain Singapore Pte Ltd., Advanced Regional Center Tampines LogisPark 1 Greenwich Drive Singapore 533865                |
| KWE Shanghai             | KWE Kintetsu World Express (China) Co., Ltd. Shanghai Pudong Airport Pilot Free Trade Zone No. 530 Zheng Ding Road Shanghai, P.R. China |
| K&N Großostheim          | Infineon Technology AG Distribution Center Europe (DCE) Kühne & Nagel Stockstädter Strasse 10 – Building 8A 63762 Großostheim Germany   |

Tabelle 4: TOE Distribution Centers

For the sites listed above, the requirements have been specifically applied in accordance with the Security Target [6]. The evaluators verified, that the threats, security objectives

and requirements for the TOE life cycle phases up to delivery (as stated in the Security Target [6] and [9]) are fulfilled by the procedures of these sites.

Note: End of report