

SAMSUNG

Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series

FIPS 140-2 Security Policy
Document Revision: 1.1

H/W version: MZILT800HAHQ-000C9, MZILT960HAHQ-000C9, MZILT1T6HAJQ-000C9, MZILT1T9HAJQ-000C9, MZILT3T2HALS-000C9, MZILT3T8HALS-000C9, MZILT7T6HMLA-000C9, MZILT15THMLA-000C9, MZILT30THMLA-000C9, MZILT800HAHQ-00AC9, MZILT960HAHQ-00AC9, MZILT1T6HAJQ-00AC9, MZILT1T9HAJQ-00AC9, MZILT3T2HALS-00AC9, MZILT3T8HALS-00AC9, MZILT7T6HMLA-00AC9, MZILT15THMLA-00AC9 and MZILT30THMLA-00AC9

F/W version: EXF7, EXV7, EZF7, EXF8, EXV8, EZF8, EXF9, EXV9, EZF9, EXFA, EXVA and EZFA

Revision History

Version	Updates
1.0	Initial Version
1.1	Minor changes as updated module version

Table of Contents

1.	Introduction	4
1.1.	Hardware and Physical Cryptographic Boundary	5
1.2.	Firmware and Logical Cryptographic Boundary	6
2.	Acronym	7
3.	Security Level Specification	8
4.	Cryptographic Functionality.....	9
4.1.	Approved algorithms.....	9
4.2.	Non-Approved Algorithm	10
4.3.	Critical Security Parameters	11
4.4.	Public Security Parameters	12
5.	Physical Ports and Logical Interfaces	13
6.	Roles, Services and Authentication	14
6.1.	Roles	14
6.2.	Authentication.....	14
6.3.	Services.....	15
6.3.1.	Authenticated Services	15
6.3.2.	Unauthenticated Services	15
7.	Physical security policy	17
8.	Electromagnetic Interference/Electromagnetic Compatibility (EMI/EMC).....	20
9.	Mitigation of Other Attacks Policy.....	21
10.	Security rules	22
10.1.	Secure Installation	22
10.2.	Operational description of Module	23
10.3.	Power-on Self-Tests	24

1. Introduction

Samsung Electronics Co., Ltd. (“Samsung”) SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series, herein after referred to as a “cryptographic module” or “module”, SSD (Solid State Drive), satisfies all applicable FIPS 140-2 Security Level 2 requirements, supporting TCG Opal SSC based SED (Self-Encrypting Drive) features, designed to protect unauthorized access to the user data stored in its NAND Flash memories. The built-in AES HW engines in the cryptographic module’s controller provide on-the-fly encryption and decryption of the user data without performance loss. The SED’s nature also provides instantaneous sanitization of the user data via cryptographic erase.

Module Name	Hardware Version	Firmware Version	Drive Capacity
Samsung SAS 12G TCG Enterprise SSC SEDs PM1643	MZILT960HAHQ-000C9 MZILT960HAHQ-00AC9	EXF7, EXF8, EXF9 and EXFA	960GB
	MZILT1T9HAJQ-000C9 MZILT1T9HAJQ-00AC9		1.9TB
	MZILT3T8HALS-000C9 MZILT3T8HALS-00AC9		3.8TB
	MZILT7T6HMLA-000C9 MZILT7T6HMLA-00AC9	EXV7, EXV8, EXV9 and EXVA	7.6TB
	MZILT15THMLA-000C9 MZILT15THMLA-00AC9		15.3TB
	MZILT30THMLA-000C9 MZILT30THMLA-00AC9	EXV7, EXV8 and EXV9	30.7TB
Samsung SAS 12G TCG Enterprise SSC SEDs PM1645	MZILT800HAHQ-000C9 MZILT800HAHQ-00AC9	EZF7, EZF8, EZF9 and EZFA	800GB
	MZILT1T6HAJQ-000C9 MZILT1T6HAJQ-00AC9		1.6TB
	MZILT3T2HALS-000C9 MZILT3T2HALS-00AC9		3.2TB

Exhibit 1 – Versions of Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series.

1.1. Hardware and Physical Cryptographic Boundary

The following photographs show the cryptographic module’s top and bottom views. The multiple-chip standalone cryptographic module consists of hardware and firmware components that are all enclosed in two aluminum alloy cases, which serve as the cryptographic boundary of the module. The top and bottom cases are assembled by screws and the tamper-evident labels are applied for the detection of any opening of the cases. No security relevant component can be seen within the visible spectrum through the opaque enclosure.

New firmware versions within the scope of this validation must be validated through the FIPS 140-2 CMVP. Any other firmware loaded into this module is out of the scope of this validation and requires a separate FIPS 140-2 validation.




Exhibit 2 – Specification of the Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series Cryptographic Boundary (From top to bottom, side).

1.2. Firmware and Logical Cryptographic Boundary

The PM1643/PM1645 series use a single chip controller with a SAS interface on the system side and Samsung NAND flash internally. The following figure depicts the Module operational environment.




Exhibit 3 – Block Diagram for Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series.

2. Acronym

Acronym	Description
CTRL	RFX Controller (SAMSUNG RFX SAS 12G TLC/MLC SSD Controller)
SAS I/F	Serial Attached SCSI Interface
CPU	Central Processing Unit (ARM-based)
DRAM I/F	Dynamic Random Access Memory Interface
ECC	Error Correcting Code
NAND I/F	NAND Flash Interface
PMIC	Power Management Integrated Circuit
ROM	Read-only Memory
DRAM	Dynamic Random Access Memory
NAND	NAND Flash Memory
LBA	Logical Block Address
MEK	Media Encryption Key
MSID	Manufactured SID(Security Identifier)

Exhibit 4 – Acronym and Descriptions for Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series.

3. Security Level Specification

Security Requirements Area	Level
Cryptographic Module Specification	2
Cryptographic Module Ports and Interfaces	2
Roles, Services, and Authentication	2
Finite State Model	2
Physical Security	2
Operational Environment	N/A
Cryptographic Key Management	2
EMI/EMC	3
Self-tests	2
Design Assurance	2
Mitigation of Other Attacks	N/A

Exhibit 5 – Security Level Table.

4. Cryptographic Functionality

4.1. Approved algorithms

The cryptographic module supports the following Approved algorithms for secure data storage:

CAVP Cert.	Algorithm	Standard	Mode / Method	Key Lengths, Curves or Moduli	Use
#5240	AES	FIPS 197 SP 800-38E	XTS	256-bit	Data Encryption / Decryption <i>*Note1</i>
Vendor Affirmed	CKG	SP800-133			Cryptographic Key Generation
#1948	DRBG	SP 800-90A Revision 1	Hash_ DRBG (SHA-256)		Deterministic Random Bit Generation
#2785	RSA	FIPS 186-4	SigVer	PSS-2048	Digital Signature Verification
#4178 #4179	SHS	FIPS 180-4	SHA-256		Message Digest

Exhibit 6 - Samsung SAS 12G TCG Enterprise SSC SED PM1643/PM1645 Series Approved Algorithms.

NOTE 1: AES-ECB is the pre-requisite for AES-XTS; AES-ECB alone is NOT supported by the cryptographic module in FIPS Mode.

NOTE 2: This module supports AES-XTS which is only approved for storage applications.

4.2. Non-Approved Algorithm

The cryptographic module supports the following non-Approved but allowed algorithms:

Algorithm	Use
NDRNG	Non-deterministic Random Number Generator (only used for generating seed materials for the Approved DRBG)

Exhibit 7 - Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series Non-Approved but allowed algorithms.

4.3. Critical Security Parameters

The cryptographic module contains the following Keys and CSPs:

CSPs	Generation, Storage and Zeroization Methods	Size
DRBG Internal State <i>*Note3</i>	Generation: SP 800-90A HASH_DRBG (SHA-256) Storage: Plaintext in DRAM Zeroization: "Initialization", "Erase an LBA Range's Data" and "Zeroize" service	V: 440-bits C: 440-bits
DRBG Seed	Generation: via NDRNG Storage: Plaintext in DRAM Zeroization: via "Initialization", "Erase an LBA Range's Data" and "Zeroize" service	Entropy input String: 440-bits Nonce: 128-bits Personalization String: 512-bits
DRBG Entropy Input String	Generation: via NDRNG Storage: Plaintext in DRAM Zeroization: via "Initialization", "Erase an LBA Range's Data" and "Zeroize" service	440-bits
CO Password	Generation: N/A Storage: Plaintext in Flash Memory and used in SRAM Zeroization: via "Initialization" and "Zeroize" service	48-256 bits
User Password	Generation: N/A Storage: Plaintext in Flash Memory and used in SRAM Zeroization: via "Initialization" and "Zeroize" service	48-256 bits
MEK	Generation: SP 800-90A Hash_DRBG (SHA-256) As per SP 800-133 Section 6.1, key generation is performed as per the "Direct Generation: of Symmetric Keys" which is an Approved key generation method Key Type: AES-XTS 256 Storage: Plaintext in Flash Memory and used in SRAM Zeroization: via "Initialization", "Lock an LBA Range", "Erase an LBA Range's Data" and "Zeroize" service	256-bits

Exhibit 8 - CSPs and details on Generation, Storage and Zeroization Methods.

Note3: The values of V and C are the "secret values" of the internal state.

NOTE 4: In accordance with FIPS 140-2 IG D.12, the cryptographic module performs Cryptographic Key Generation (CKG) as per SP 800-133 (Vendor Affirmed). The resulting generated symmetric key is the unmodified output from SP 800-90A DRBG.

4.4. Public Security Parameters

Public Keys	Generation, Storage and Zeroization Methods
FW Verification Key (RSA Public Key)	Generation: N/A Key Type: RSA 2048-PSS Storage: Plaintext in Flash Memory and used in SRAM Zeroization: N/A

Exhibit 8 - Public Keys and details on Generation, Storage and Zeroization Methods

5. Physical Ports and Logical Interfaces

Physical Port	Logical Interface
SAS Connector	Data Input/Output Control Input Status Output Power Input

Exhibit 9 - Specification of the Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series Cryptographic Module Physical Ports and Logical Interfaces.

6. Roles, Services and Authentication

6.1. Roles

The following table defines the roles, type of authentication, and associated authenticated data types supported by the cryptographic module:

Role	Authentication Data
CO Role	Password
User Role	Password
FW Loader	RSA

Exhibit 10 - Roles and Required Identification and Authentication

6.2. Authentication

The authentication mechanism allows 6-byte length or longer (32-byte) Password, where each byte can be any of 0x00 to 0xFF, for every Cryptographic Officer and User role supported by the module, which means a single random attempt can succeed with the probability of $1/2^{48}$ or lower.

Each authentication attempt takes at least 1ms and the number of attempts is limited to TryLimit, which is set to 33 in manufacturing time. Since the module takes at least 4 seconds to be ready after power-on and 33 authentication failures require a power-cycle, it takes 4033ms for every 33rd authentication attempt. Therefore, the probability of multiple random attempts to succeed in one minute is $495 / 2^{48}$, which is much less than the FIPS 140-2 requirement $1/100,000$. Even if the TryLimit is greater than 33, the probability of random attempts always satisfies the requirement.

The authentication mechanism for FW Loader role is RSA PSS-2048 with SHA256 digital signature verification, which means a single random attempt, can succeed with the probability of $1/2^{112}$.

Each RSA Signature Verification authentication attempt takes at least 50ms. So the number of attempts for one minute cannot exceed $1200((60*1000)/50)$. Therefore, the probability of multiple random attempts to succeed in one minute is $1200/2^{112}$, which is much less than the FIPS 140-2 requirement $1/100,000$.

Authentication Mechanism	Strength of Mechanism
Password (Min: 6 bytes, Max: 32 bytes) Authentication	<ul style="list-style-type: none"> - Probability of $1/2^{48}$ in a single random attempt - Probability of $495/2^{48}$ in multiple random attempts in a minute
RSA Signature Verification	<ul style="list-style-type: none"> - Probability of $1/2^{112}$ in a single random attempt - Probability of $1200/2^{112}$ in multiple random attempts in a minute

Exhibit 11 Strengths of Authentication Mechanisms

6.3. Services

6.3.1. Authenticated Services

The following table lists roles, services, cryptographic keys, CSPs and Public Keys and the types of access that are available to each of the authorized roles via the corresponding services:

* Type(s) of Access indicated using “O” marker.

* R: READ; W: WRITE; G: GENERATE; Z: ZEROIZE

Role	Service	Cryptographic Keys, CSPs and Public Keys	Security Function	Type(s) of Access			
				R	W	G	Z
Cryptographic Officer	Initialization	DRBG Internal State	Hash_	O		O	O
		DRBG Seed	DRBG	O		O	O
		DRBG Entropy Input String	(SHA-256)	O		O	O
		CO Password			O		O
		MEK				O	O
	Drive Extended Status	N/A	N/A	N/A			
	Admin/User Authority Enable/Disable	N/A	N/A	N/A			
	Lock an LBA Range	MEK	N/A				O
	Unlock an LBA Range	MEK	AES-XTS	O			
	Configure an LBA Range	N/A	N/A	N/A			
	Erase an LBA Range’s Data	DRBG Internal State	Hash_	O		O	O
		DRBG Seed	DRBG	O		O	O
		DRBG Entropy Input String	(SHA-256)	O		O	O
		MEK				O	O
		User Password			O		O
	Zeroize	DRBG Internal State	Hash_				O
		DRBG Seed	DRBG				O
		DRBG Entropy Input String	(SHA-256)				O
		CO Password					O
		User Password					O
MEK						O	
User	Unlock an LBA Range	MEK	AES-XTS	O			
	Set User Password	User Password	N/A		O		
	Lock an LBA Range	MEK	N/A			O	
	Configure an LBA Range	N/A	N/A	N/A			
FW Loader	Update the firmware	FW Verification Key	RSA SigVer, SHA-256	O			

Exhibit 12 - Services Authorized for Roles, Access Rights within Services

6.3.2. Unauthenticated Services

The following table lists the unauthenticated services:

* Type(s) of Access indicated using “O” marker.

* R: READ; W: WRITE; G: GENERATE; Z: ZEROIZE

Unauthenticated Service	Cryptographic Keys & CSPs	Security Function	Type(s) of Access			
			R	W	G	Z
Zeroize	DRBG Internal State	Hash_ DRBG (SHA-256)				O
	DRBG Seed					O
	DRBG Entropy Input String					O
	CO Password					O
	User Password					O
	MEK					O
Get Random Number	DRBG Internal State	Hash_ DRBG (SHA-256)	O		O	O
	DRBG Seed		O		O	O
	DRBG Entropy Input String		O		O	O
Get MSID	N/A	N/A	N/A			
Show Status	N/A	N/A	N/A			
Self-test	N/A	N/A	N/A			

Exhibit 13 – Unauthenticated Service, Cryptographic Keys & CSPs and Type(s) of Access.

7. Physical security policy

The following physical security mechanisms are implemented in a cryptographic module:

- The Module consists of production-grade components enclosed in an aluminum alloy enclosure, which is opaque within the visible spectrum. The top panel of the enclosure can be removed by unscrewing screws. However, the module is sealed with tamper-evident labels in accordance with FIPS 140-2 Level 2 Physical Security requirements so that tampering is easily detected when the top and bottom cases are detached.
- 2 tamper-evident labels are applied over both top and bottom cases of the module at the factory. The tamper-evident labels are not removed and reapplied without tamper evidence.

The following table summarizes the actions required by the Cryptographic Officer Role to ensure that physical security is maintained:

Physical Security Mechanisms	Recommended Frequency of Inspection/Test	Inspection/Test Guidance Details
Production grade cases	As often as feasible	Inspect the entire perimeter for cracks, gouges, lack of screw(s) and other signs of tampering. Remove from service if tampering found.
Tamper-evident Sealing Labels		Inspect the sealing labels for scratches, gouges, cuts and other signs of tampering. Remove from service if tampering found.

Exhibit 14 - Inspection/Testing of Physical Security Mechanisms

Samsung SAS 12G TCG Enterprise SSC SEDs PM1643/PM1645 Series



Exhibit 15 - Signs of Tamper

NOTE 5: Samsung Electronics Co., Ltd has excluded the following components as per AS01.09:

Items	BOM Code	Applicable to Hardware Version(s)
Resistor	2007-007136	MZILT800HAHQ-000C9, MZILT960HAHQ-000C9, MZILT800HAHQ-00AC9, MZILT960HAHQ-00AC9
Resistor	2007-000972	MZILT800HAHQ-000C9, MZILT960HAHQ-000C9, MZILT1T6HAJQ-000C9, MZILT1T9HAJQ-000C9, MZILT3T2HALS-000C9, MZILT3T8HALS-000C9, MZILT7T6HMLA-000C9, MZILT800HAHQ-00AC9, MZILT960HAHQ-00AC9, MZILT1T6HAJQ-00AC9, MZILT1T9HAJQ-00AC9, MZILT3T2HALS-00AC9, MZILT3T8HALS-00AC9, MZILT7T6HMLA-00AC9
Resistor	2007-000033	MZILT1T6HAJQ-000C9, MZILT1T9HAJQ-000C9, MZILT3T2HALS-000C9, MZILT3T8HALS-000C9, MZILT7T6HMLA-000C9, MZILT1T6HAJQ-00AC9, MZILT1T9HAJQ-00AC9, MZILT3T2HALS-00AC9, MZILT3T8HALS-00AC9, MZILT7T6HMLA-00AC9
Capacitor	2203-009818	MZILT800HAHQ-000C9, MZILT960HAHQ-000C9, MZILT1T6HAJQ-000C9, MZILT1T9HAJQ-000C9, MZILT3T2HALS-000C9, MZILT3T8HALS-000C9, MZILT7T6HMLA-000C9, MZILT15THMLA-000C9, MZILT30THMLA-000C9, MZILT800HAHQ-00AC9, MZILT960HAHQ-00AC9, MZILT1T6HAJQ-00AC9, MZILT1T9HAJQ-00AC9, MZILT3T2HALS-00AC9, MZILT3T8HALS-00AC9, MZILT7T6HMLA-00AC9, MZILT15THMLA-00AC9, MZILT30THMLA-00AC9
Capacitor	2203-008953	MZILT800HAHQ-000C9, MZILT960HAHQ-000C9, MZILT1T6HAJQ-000C9, MZILT1T9HAJQ-000C9, MZILT3T2HALS-000C9, MZILT3T8HALS-000C9, MZILT7T6HMLA-000C9, MZILT15THMLA-000C9, MZILT30THMLA-000C9, MZILT800HAHQ-00AC9, MZILT960HAHQ-00AC9, MZILT1T6HAJQ-00AC9, MZILT1T9HAJQ-00AC9, MZILT3T2HALS-00AC9, MZILT3T8HALS-00AC9, MZILT7T6HMLA-00AC9, MZILT15THMLA-00AC9, MZILT30THMLA-00AC9
Capacitor	2203-009815	MZILT15THMLA-000C9, MZILT30THMLA-000C9, MZILT15THMLA-00AC9, MZILT30THMLA-00AC9
Capacitor	2203-000206	MZILT15THMLA-000C9, MZILT30THMLA-000C9, MZILT15THMLA-00AC9, MZILT30THMLA-00AC9
Capacitor	2203-009805	MZILT30THMLA-000C9, MZILT30THMLA-00AC9
Storage IC	K9DVBG8JBM-7###	MZILT30THMLA-000C9, MZILT30THMLA-00AC9

Exhibit 16 – Excluded components

The above power electronics are used for MLCC power and do not process any CSPs, Plaintext data, or other information that if misused could lead to compromise.

8. Electromagnetic Interference/Electromagnetic Compatibility (EMI/EMC)

The cryptographic module conforms to the EMI/EMC requirements specified by 47 Code of Federal Regulations, Part 15, Subpart B, Unintentional Radiators, Digital Devices, Class B.

9. Mitigation of Other Attacks Policy

The cryptographic module has not been designed to mitigate any specific attacks beyond the scope of FIPS 140-2.

Other Attacks	Mitigation Mechanism	Specific Limitations
N/A	N/A	N/A

Exhibit 17 - Mitigation of Other Attacks

10. Security rules

The following specifies the security rules under which the cryptographic module shall operate in accordance with FIPS 140-2:

- The cryptographic module operates always in FIPS Mode once shipped from the vendor's manufacturing site.
- The steps necessary for the secure installation, initialization and start-up of the cryptographic module as per FIPS 140-2 VE10.03.01 are as follows:

10.1. Secure Installation

- [Step1] User should examine the tamper evidence
 - Inspect the entire perimeter for cracks, gouges, lack of screw(s) and other signs of tampering including the tamper evident sealing label.
 - If there is any sign of tampering, do not use the product and contact Samsung.
- [Step2] Identify the firmware version in the device
 - Confirm that the firmware version is equivalent to the version(s) listed in this document via SCSI Inquiry command.
- [Step3] Take the drive's ownership
 - Change SID's PIN by setting a new PIN
 - Change EraseMaster's PIN by setting a new PIN
 - Erase Method on each LBA Range to rekey the encryption key
 - Change BandMaster0~7's PIN by setting new PINs
 - Configure the LBA Range(s) by setting ReadLockEnabled and WriteLockEnabled columns to True
 - Don't change LockOnReset column in Locking Table so that the drive always gets locked after a power cycle
- [Step4] Configure FW download and Diagnostic features
 - Disable Makers Class using SID Authority to disable FW download and Diagnostic features
 - Enable Makers Class only when FW download and Diagnostic features are needed
- [Step5] Periodically examine the tamper evidence
 - If there is any sign of tampering, stop using the product to avoid a potential security hazard or information leakage.

10.2. Operational description of Module

- The cryptographic module shall maintain logical separation of data input, data output, control input, status output, and power.
- The cryptographic module shall not output CSPs in any form.
- The cryptographic module shall use the Approved DRBG for generating all cryptographic keys.
- The cryptographic module shall enforce role-based authentication for security relevant services.
- The cryptographic module shall enforce a limited operational environment by the secure firmware load test using RSA PSS-2048 with SHA-256.
- The cryptographic module shall provide a production-grade, opaque, and tamper-evident cryptographic boundary.
- The cryptographic module enters the error state upon failure of Self-tests. All commands from the Host (General Purpose Computer (GPC) outside the cryptographic boundary) are rejected in the error state and the cryptographic module returns a sense key (0x4) via the status output. Cryptographic services and data output are explicitly inhibited when in the error state.
- The cryptographic module satisfies the requirements of FIPS 140-2 IG A.9 (i.e. key_1 ≠ key_2)
- The module generates at a minimum 256 bits of entropy for use in key generation.

10.3. Power-on Self-Tests

Algorithm	Test
AES	Encrypt KAT and Decrypt KAT for AES-256-XTS at power-on
SHS (Cert. #4178)	KAT for SHA-256 at power-on
SHS (Cert. #4179)	KAT for SHA-256 at power-on
DRBG	KAT for Hash_DRBG (SHA-256) at power-on
RSA	Firmware integrity check using RSA PSS-2048 SHA-256 signature verification at power-on

Exhibit 18 – Power-on Self-tests.

▪ **Conditional Self-test**

- Pairwise consistency: N/A
- Bypass Test: N/A
- Manual key entry test: N/A
- F/W load test
 - F/W load test is performed by using RSA algorithm with PSS-2048 and SHA-256
- Continuous random number generator test on Approved DRBG
- Continuous random number generator test on NDRNG