



ENTRUST

SECURING A WORLD IN MOTION

nShield Solo XC F3 & nShield Solo XC F3 for nShield Connect XC and for nShield HSMⁱ

Non-proprietary Security Policy for FIPS 140-
2 Level 3

Version: 1.1.1

Date: 30/01/2024

Copyright © 2020 nCipher Security Limited. All rights reserved.

Copyright in this document is property of nCipher Security Limited. This document may be reproduced and distributed in whole (i.e., without modification) provided that the copyright notice and Entrust branding has not been removed or altered.

Words and logos marked with ® or ™ are trademarks of nCipher Security Limited or its affiliates in the EU and other countries.

Mac and OS X are trademarks of Apple Inc., registered in the U.S. and other countries.

Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Information in this document is subject to change without notice.

nCipher Security Limited makes no warranty of any kind with regard to this information, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. nCipher Security Limited shall not be liable for errors contained herein or for incidental or consequential damages concerned with the furnishing, performance or use of this material.

Where translations have been made in this document English is the canonical language.

nCipher Security Limited
Registered Office: One Station Square,
Cambridge, CB1 2GA, United Kingdom
Registered in England No. 11673268

nCipher is an Entrust company.

Entrust, Datacard, and the Hexagon Logo are trademarks, registered trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer.

Contents

1	Introduction	4
1.1	Scope.....	4
1.2	Security level.....	4
1.3	Cryptographic module description	5
1.4	Operational environment.....	6
2	Cryptographic Functionality.....	7
2.1	Security World overview.....	7
2.2	Keys and Critical Security Parameters.....	8
2.3	Supported cryptographic algorithms.....	15
3	Roles and Services.....	23
3.1	Roles	23
3.2	Strength of authentication mechanisms	24
3.3	Services.....	24
4	Physical Security.....	35
5	Rules.....	36
5.1	Delivery.....	36
5.2	Initialization procedures.....	36
5.3	Creation of new Operators.....	36
6	Self tests.....	38
6.1	Power-up self-tests	38
6.2	Conditional self-tests.....	39
6.3	Firmware load test.....	39
	Contact Us	40

1 Introduction

1.1 Scope

This document defines the non-proprietary Security Policy enforced by the nShield Hardware Security Module, i.e. the Cryptographic Module, to meet with the security requirements in FIPS 140-2.

The following product hardware variants and firmware version(s) are in scope of this Security Policy.

Variant name	Marketing model number	Firmware version
nShield Solo XC F3	nC4035E-000	12.72.1 12.72.3
nShield Solo XC F3 for nShield Connect XC and for nShield HSMi	nC4335N-000 ¹	

Table 1 Variants

¹ This module is embedded in the nShield Connect XC appliance with model numbers NH2075-x, NH-2089-x (where x is B, M or H) or in the nShield HSMi with model numbers NH2089-8k-ISS, NH2089-16k-ISS (where x is B, M or H)

All modules are supplied at build standard “A”

1.2 Security level

The Cryptographic Module meets overall FIPS 140-2 Security Level 3. The following table specifies the security level in detail.

Security requirements section	Level
Cryptographic Module Specification	3
Module Ports and Interfaces	3
Roles, Services and Authentication	3
Finite State Model	3
Physical Security	3
Operational Environment	N/A
Cryptographic Key Management	3

Security requirements section	Level
EMI/EMC	3
Self-Tests	3
Design Assurance	3
Mitigation of Other Attacks	N/A

Table 2 Security level of security requirements

1.3 Cryptographic module description

The nShield Hardware Security Module (HSM) is a multi-chip embedded Cryptographic Module as defined in FIPS 140-2, which comes in a PCI express board form factor protected by a tamper resistant enclosure, and performs encryption, digital signing, and key management on behalf of an extensive range of commercial and custom-built applications including public key infrastructures (PKIs), identity management systems, application-level encryption and tokenization, SSL/TLS, and code signing.

The nShield Solo XC HSM is also embedded inside the nShield Connect XC and the nShield HSM*i*, which are network-attached appliance delivering cryptographic services as a shared network resource for distributed applications and virtual machines, giving organizations a highly secure solution for establishing physical and logical controls for server-based systems.

The table below shows the nShield Solo XC HSM, the nShield Connect XC and the nShield HSM*i* appliances.



Table 3 nShield Solo XC (left), nShield Connect XC (centre), and nShield HSM*i* (right)

The cryptographic boundary is delimited in red in the images in the table below. It is delimited by the heat sink and the outer edge of the potting material on the top and bottom of the PCB.

The Cryptographic Module provides the following physical ports and interfaces, which remain outside of the cryptographic boundary:

- PCIe bus (data input/output, control input, status output and power). The services provided by the module are transported through this interface.

- Status LED (status output)
- Mode switch (control input)
- Clear button (control input)
- PS/2 serial connector for connecting a smartcard reader (data input/output).
- 14-way header (data input/output, control input, status output) which provides alternative connections for the mode switch, clear button, status LED and serial connector.
- Dual configuration switches (control input), are a set of two jumpers which enable the mode switch and enable the remote mode switching.
- Battery (power), providing power backup.
- Heat fan control signal.

The PCB traces coming from those connectors transport the signals into the module's cryptographic boundary and cannot be used to compromise the security of the module.

The top cover, heat fan and the battery are outside the module's cryptographic boundary and cannot be used to compromise the security of the module.




Table 4 Cryptographic module boundary

1.4 Operational environment

The FIPS 140-2 Operational Environment requirements are not applicable because the cryptographic module contains a limited operational environment.

2 Cryptographic Functionality

2.1 Security World overview

The security model of the module is based around the Security World concept for secure management of cryptographic keys.

A Security World includes:

- An Administrator Card Set (ACS), a set of Administrator smart cards used to perform administrative operations,
- Optionally, one or more Operator Card Sets (OCSs), a set or sets of Operator smart cards used to control access to application keys and to authorise certain operations,
- Optionally, a set of Softcards used to control access to application keys,
- Key Blobs, which contain cryptographic keys and their associated Access Control List (ACL), whose confidentiality and integrity are protected by approved algorithms. They are stored outside the Cryptographic Module.

2.2 Keys and Critical Security Parameters

The Cryptographic Module uses and protects the following keys and Critical Security Parameters (CSPs):

CSP	Type	Description	Generation	Input	Output	Storage	Zeroization
KRE - Recovery Confidentiality Key	RSA 3072-bit	Key used to protect recovery keys (KR). KTS cert# A1931	DRBG	Load Blob - encrypted with LT	Make Blob - encrypted with LT	Ephemeral, stored in volatile RAM.	Initialize Unit
KR - Recovery Key	AES 256-bit	Key used to derive (using SP 800-108 KDF in counter mode) the keys Ke (AES 256-bit) and Km (HMAC-SHA256) that protect an archive copy of an application key. <ul style="list-style-type: none">AES cert #A1931	DRBG	Load Blob - encrypted with KRE	Make Blob - encrypted with KRE	Ephemeral, stored in volatile RAM.	Initialize Unit, Clear Unit, power cycle or reboot.
Impath session keys	AES 256-bit in CBC mode. Integrity with HMAC SHA-256.	Used for secure channel between two modules. It consists of a set of four session keys used in an Impath session for encryption, decryption, MAC generation and MAC validation. <ul style="list-style-type: none">AES cert #A1931HMAC cert #A1931	3072-bit DH key exchange	No	No	Ephemeral, stored in volatile RAM.	Clear Unit, new session, power cycle or reboot.
KJSO - JSO key	DSA 3072-bit	nShield Junior Security Officer key used with its associated certificate to perform the operations allowed by the NSO.	DRBG	Load Blob - encrypted with LT	Make Blob - encrypted with LT	Ephemeral, stored in	Destroy, Initialize Unit, Clear Unit,

CSP	Type	Description	Generation	Input	Output	Storage	Zeroization
		<ul style="list-style-type: none"> DSA cert #A1931 				volatile RAM.	power cycle or reboot.
KA - Application key	<p>AES 128, 192, 256 bits</p> <p>HMAC with key sizes >= 112 bits</p> <p>RSA with key sizes >= 2048 bits</p> <p>DSA, DH with key sizes >= 2048 bits</p> <p>ECDSA, ECDH, EC MQV with curves:</p> <ul style="list-style-type: none"> P-224, P-256, P-384, P-521 K-233, K-283, K-409, K-571 B-233, B-283, B-409, B-571 Brainpool 	<p>Keys associated with a user to perform cryptographic operations, that can be used with one of the following validated algorithms:</p> <ul style="list-style-type: none"> AES and KTS cert #A1931 HMAC cert #A1931 RSA cert #A1931 DSA cert #A1931 ECDSA cert #A1931 Key Agreement (KAS) cert #A1931 KBKDF cert #A1931 KTS cert #A1931 	DRBG	Load Blob - encrypted with LT or KR	Make Blob - encrypted with LT or KR	Ephemeral, stored in volatile RAM.	Destroy, Initialize Unit, Clear Unit, power cycle or reboot

CSP	Type	Description	Generation	Input	Output	Storage	Zeroization
KM - Module Key	AES 256-bit	Key used to protect logical tokens and associated module Key Blobs. <ul style="list-style-type: none"> AES cert #A1931 	DRBG	Load Blob - encrypted with LT	Make Blob - encrypted with LT	Non-volatile memory	Initialize Unit
KML - Module Signing Key	DSA 3072-bit	Module Signing Key used by the module to sign key generation and module state certificates. <p>When the nShield module is initialized, it automatically generates this key that it uses to sign certificates using DSA with SHA-256. This key is only ever used to verify that a certificate was generated by a specific module.</p> <ul style="list-style-type: none"> DSA cert #A1931 	DRBG	No	No	Non-volatile memory	Initialize Unit
KNSO - NSO key	DSA 3072-bit	nShield Security Officer key used for NSO authorisation and Security World integrity. Used to sign Delegation Certificates and to directly authorize commands during recovery operations <ul style="list-style-type: none"> DSA cert #A1931 	DRBG	Load Blob - encrypted with LT	Make Blob - encrypted with LT	Ephemeral, stored in volatile RAM.	Destroy, Initialize Unit, Clear Unit, power cycle or reboot.
LT - Logical Token	AES 256-bit	Key used to derive the keys that are used to protect token protected key blobs. Logical Tokens are split in shares (encrypted with Share Key) between one or more smartcards or a softcard, using the Shamir Secret Sharing scheme. <ul style="list-style-type: none"> AES cert #A1931 	DRBG	Read Share - encrypted with Share Key	Write Share - encrypted with Share Key	Ephemeral, stored in volatile RAM.	Destroy, Initialize Unit, power cycle or reboot

CSP	Type	Description	Generation	Input	Output	Storage	Zeroization
		<ul style="list-style-type: none"> KBKDF cert #A1931 HMAC cert #A1931 					
Share Key	AES 256-bit	<p>Protects a share when written to a smartcard or softcard. This key is used to derive (using SP 800-108 AES CTR KDF) the keys K_e (AES 256-bit) and K_m (HMAC-SHA256) that wrap the share.</p> <ul style="list-style-type: none"> AES cert #A1931 KBKDF cert #A1931 HMAC cert #A1931 	DRBG	No	No	Ephemeral, stored in volatile RAM.	N/A
Remote Administration session keys	AES 256-bit in CBC mode Integrity with CMAC	<p>Used for secure channel between the module and a smartcard. This is a set of four AES 256-bit session keys, namely K_{m-e} (for encrypting data send to the smartcard), K_{c-e} (for decrypting data from the smartcard), K_{m-a} (for CMAC generation) and K_{c-a} (for CMAC verification).</p> <ul style="list-style-type: none"> AES cert #A1931 	ECDH P-521 key agreement	No	No	Ephemeral, stored in volatile RAM.	Clear Unit, new session, power cycle or reboot.
KAL - Key Audit Logging	DSA 3072-bit	<p>Used for signing the log trail.</p> <ul style="list-style-type: none"> DSA cert #A1931 	DRBG	No	No	Non-volatile memory	Initialize Unit
DRBG internal state	Hash_DRBG	<p>The module uses the Hash_DRBG with SHA-256 compliant with SP800-90A.</p> <ul style="list-style-type: none"> Hash DRBG cert #A1931 	Entropy source	No	No	Ephemeral, stored in	Clear Unit, power cycle or reboot.

CSP	Type	Description	Generation	Input	Output	Storage	Zeroization
						volatile RAM.	
DRBG entropy input	344 bits	Entropy input string used to initialize and re-seed the DRBG.	Entropy source	No	No	Ephemeral, stored in volatile RAM.	Clear Unit, power cycle or reboot.

Table 5 CSP table

The following table describes the public keys handled by the module:

Public Key	Type	Description	Generation	Input	Output	Storage
Firmware Integrity key (KFI)	ECDSA P-521	Public key used to ensure the integrity of the firmware during boot. The module validates the signature before new firmware is written to non-volatile storage. <ul style="list-style-type: none"> • ECDSA 805 	At Entrust	Firmware update	No	In firmware
KJWAR	ECDSA P-521	Entrust root warranting public key for Remote Administrator Cards and Remote Operator Cards <ul style="list-style-type: none"> • ECDSA cert #A1931 	At Entrust	Firmware update	None	Persistent storage in plaintext inside the module (EEPROM)
Application keys public key	See description	Public keys associated with private Application keys: <ul style="list-style-type: none"> • RSA cert #A1931 	At creation of the	Load Blob - encrypted with LT	Key export	Stored in the key blob of the application key

Public Key	Type	Description	Generation	Input	Output	Storage
		<ul style="list-style-type: none"> • DSA cert #A1931 • ECDSA cert #A1931 • Key Agreement (KAS) cert #A1931 • KTS cert #A1931 	application key			
KJSO public key	DSA 3072-bit	Public key associated to KJSO <ul style="list-style-type: none"> • DSA cert #A1931 	At creation of the KJSO	Load Blob - encrypted with LT	Key export	Public key hash stored in the module persistent storage
KNSO public key	DSA 3072-bit	Public key associated to KNSO <ul style="list-style-type: none"> • DSA cert #A1931 	At creation of the KNSO	Load Blob - encrypted with LT	Key export	Public key hash stored in the module persistent storage
KML public key	DSA 3072-bit	Public key associated to KML <ul style="list-style-type: none"> • DSA cert #A1931 	At creation of KML	No	Key export	Public key hash stored in the module persistent storage
KAL public key	DSA 3072-bit	Public key associated to KAL <ul style="list-style-type: none"> • DSA cert #A1931 	At creation of KAL	No	Included in the audit trail	Public key hash stored in the module persistent storage
KRE public key	RSA 3072-bit	Public key associated to KRE <ul style="list-style-type: none"> • KTS cert #A1931 	At creation of the KNSO	Load Blob - encrypted with LT	Key export	Stored in a key blob

Public Key	Type	Description	Generation	Input	Output	Storage
FET public key	DSA 1024-bit	Feature Enable Tool (FET) public key used to verify FET certificates <ul style="list-style-type: none"> • DSA cert #A1931 	At Entrust	Firmware update	No	Persistent storage in plaintext inside the module (EEPROM)
Impath DH public key	DH 3072-bit	Public key from peer used in the Impath DH key agreement. <ul style="list-style-type: none"> • KAS cert #A1931 	No	Loaded with Cmd_ImpathKXFinish	No	Ephemeral, stored in volatile RAM.
Remote Administration ECDH public key	NIST P-521	Public key from peer used in the Remote Administration ECDH key agreement. <ul style="list-style-type: none"> • KAS cert #A1931 	No	Loaded with Cmd_DynamicSlotExchangeAPDUs	No	Ephemeral, stored in volatile RAM.

Table 6 Public key table

2.3 Supported cryptographic algorithms

2.3.1 FIPS Approved or Allowed Algorithms

The following tables describe the Approved or allowed cryptographic algorithms supported by the Cryptographic Module.

Cert #	Algorithm and mode	Standard	Key sizes	Use
A1931	Advanced Encryption Standard (AES) <ul style="list-style-type: none"> • ECB • CBC • CTR • GCM 	FIPS 197 SP800-38A SP800-38D	128 bits 192 bits 256 bits	Data encryption/decryption
A1931	KTS <ul style="list-style-type: none"> • AES Key Wrapping (AES KW) • AES Key Wrapping with Padding (AES KWP) • AES GCM 	SP800-38F SP800-38D	128 bits 192 bits 256 bits	Key wrapping/unwrapping
A1931	KTS <ul style="list-style-type: none"> • RSA OAEP 	SP 800-56Brev2	2048 bits 3072 bits 4096 bits Caveat: Cert. #A1931 key establishment methodology provides between 112 and 152 bits of encryption strength.	Key transport (encapsulation, un-encapsulation)

Cert #	Algorithm and mode	Standard	Key sizes	Use
A1931	RSA <ul style="list-style-type: none"> • PKCS#1 v1.5 • PSS 	FIPS 186-4	1024 bits (verification only) 2048 bits 3072 bits 4096 bits	Key generation Signature generation and verification
A1931	Elliptic Curve Digital Signature Algorithm (ECDSA)	FIPS 186-4	<ul style="list-style-type: none"> • NIST P-224, P-256, P-384, P-521 • NIST K-233, K-283, K-409, K-571 • NIST B-233, B-283, B-409, B-571 	Signature generation and verification
A1931	Digital Signature Algorithm (DSA)	FIPS 186-4	L = 1024 bits, N = 160 bits (verification only) L = 2048 bits, N = 224 bits L = 2048 bits, N = 256 bits L = 3072 bits, N = 256 bits	Signature generation and verification
A1931	HMAC-SHA1 HMAC-SHA2	FIPS 198-1	>= 112 bits	MAC generation and verification
A1931	Advanced Encryption Standard (AES) <ul style="list-style-type: none"> • CMAC 	SP800-38B	128 bits 192 bits 256 bits	MAC generation and verification

Cert #	Algorithm and mode	Standard	Key sizes	Use
A1931	KAS-FFC <ul style="list-style-type: none"> Diffie-Hellman (DH) 	SP 800-56Arev3	MODP-2048 MODP-3072 MODP-4096 MODP-6144 MODP-8192 FB FC	Key establishment
A1931	KAS-ECC <ul style="list-style-type: none"> Elliptic Curve Diffie-Hellman (ECDH) 	SP 800-56Arev3	<ul style="list-style-type: none"> NIST P-224, P-256, P-384, P-521 NIST K-233, K-283, K-409, K-571 NIST B-233, B-283, B-409, B-571 	Key establishment
A1931	KAS-ECC <ul style="list-style-type: none"> Elliptic Curve Menezes–Qu–Vanstone (ECMQV) 	SP 800-56Arev3	<ul style="list-style-type: none"> NIST P-224, P-256, P-384, P-521 NIST K-233, K-283, K-409, K-571 NIST B-233, B-283, B-409, B-571 	Key establishment
A1931	Key Based KDF (KBKDF): <ul style="list-style-type: none"> counter mode 	SP 800-108	n/a	Key derivation

Cert #	Algorithm and mode	Standard	Key sizes	Use
A1931	SHA-1, SHA-224, SHA-256, SHA-384, SHA-512	FIPS 180-4	n/a	Message digest
A1931	Hash-based DRBG	SP 800-90A	n/a	Random bit generation
ENT (P)	Hardware based entropy source <i>This cryptographic module has been validated for compliance with NIST SP 800-90B. Based on noise source testing and analysis, the estimated minimum amount of entropy per the source output bit is about 0.915 bits. The overall amount of generated entropy meets the required security strength of 256 bits based on the entropy per bit and amount of entropy requested by the module.</i>	SP800-90B	n/a	Random bit generation
Vendor affirmed	CKG	SP800-133	Symmetric keys are generated using the unmodified output of the approved DRBG.	Key generation
Bootloader				
SHS 3130	SHA-256, SHA-512	FIPS 180-4	n/a	Message digest
ECDSA 805	Elliptic Curve Digital Signature Algorithm (ECDSA)	FIPS 186-4	NIST P-521	Signature verification

Table 7 Approved algorithms

Cert #	Algorithm and mode	Standard	Key sizes	Use
A1931	Elliptic Curve Digital Signature Algorithm (ECDSA) using non-NIST elliptic curves	FIPS 186-4 RFC 5639	<ul style="list-style-type: none"> • brainpoolP224r1/P224t1 (112 bits of strength) • brainpoolP256r1/P256t1 (128 bits of strength) • brainpoolP320r1/P320t1 (160 bits of strength) • brainpoolP384r1/P384t1 (192 bits of strength) • brainpoolP512r1/P512t1 (256 bits of strength) 	Signature generation and verification
A1931	EC Diffie-Hellman using non-NIST elliptic curves	SP 800-56Arev3 RFC 5639	<ul style="list-style-type: none"> • brainpoolP224r1/P224t1 (112 bits of strength) • brainpoolP256r1/P256t1 (128 bits of strength) • brainpoolP320r1/P320t1 (160 bits of strength) • brainpoolP384r1/P384t1 (192 bits of strength) • brainpoolP512r1/P512t1 (256 bits of strength) 	Key establishment
A1931	EC MQV using non-NIST elliptic curves	SP 800-56Arev3 RFC 5639	<ul style="list-style-type: none"> • brainpoolP224r1/P224t1 (112 bits of strength) 	Key establishment

Cert #	Algorithm and mode	Standard	Key sizes	Use
			<ul style="list-style-type: none"> • brainpoolP256r1/P256t1 (128 bits of strength) • brainpoolP320r1/P320t1 (160 bits of strength) • brainpoolP384r1/P384t1 (192 bits of strength) • brainpoolP512r1/P512t1 (256 bits of strength) 	

Table 8 Allowed algorithms

2.3.2 Non-Approved Algorithms

The following table describes the non-approved cryptographic algorithms supported by the Cryptographic Module in non-Approved mode.

Algorithm
Symmetric encryption and decryption
DES
Triple DES encryption, MAC generation
AES GCM with externally generated IV
AES CBC MAC
Aria
Camellia

Algorithm
Arc Four (compatible with RC4)
CAST 256 (RFC2612)
SEED (Korean Data Encryption Standard)
Asymmetric
KTS-OAEP-basic with SHA-256 with key size less than 2048 bits
ElGamal (encryption using Diffie-Hellman keys)
KCDSA (Korean Certificate-based Digital Signature Algorithm)
RSA digital signature generation with SHA-1 or key size less than 2048 bits
DSA digital signature generation with SHA-1 or key size less than 2048 bits
ECDSA digital signature generation with SHA-1 or curves P-192, K-163 , B-163
DH with key size $p < 2048$ bits or $q < 224$ bits, or non-compliant with SP800-56Arev3
ECDH with curves P-192, K-163, B-163, or non-compliant with SP800-56Arev3
EC MQV with curves P-192, K-163 or B-163, or non-compliant with SP800-56Arev3
Deterministic DSA compliant with RFC6979
Ed25519 public-key signature
X25519 key exchange
ECIES encryption/wrapping and decryption/unwrapping
ECKA-EG key agreement

Algorithm
Hash
HAS-160
MD5
RIPEMD-160
Tiger
Message Authentication Codes
HMAC with MD5, RIPEMD-160 and Tiger
HMAC with key size less than 112 bits
Other
PKCS#8 padding
EMV support: Cryptogram (ARQC) generation and verification (includes EMV2000, M/Chip 4 and Visa Cryptogram Version 14, EMV 2004, M/Chip 2.1, Visa Cryptogram Version 10) Watchword generation and verification
Hyperledger client side KDF

Table 9 Non-approved algorithms

3 Roles and Services

3.1 Roles

The Cryptographic Module supports the following roles:

- nShield Security Officer (NSO)
- Junior Security Officer (JSO)
- User

nShield Security Officer (NSO)

This role is represented by Administrator Card holders, which have access to KNSO and are responsible for the overall management of the Cryptographic Module.

To assume this role, an operator or group of operators need to present a quorum m of N of smartcards, and the KNSO Key Blob. Each operator is identified by its individual smartcard, which contains a unique logical token share.

Junior Security Officer (JSO)

This role is represented by either Administrator Card or Operator Card holders with a KJSO and an associated Delegation Certificate signed by KNSO, authorising a set of commands.

To assume this role, an operator or group of operators need to present a quorum m of N of smartcards and the associated Delegation Certificate. Each operator is identified by its individual smartcard or Softcard, which contains a unique logical token share.

User

This role is represented by Application key owners, which are authorised to perform approved services in the module using those keys.

To assume this role, an operator or group of operators need to present a quorum m of N of smartcards or a Softcard, and the Key Blob. Each operator is identified by its individual Smartcard or Softcard, which contains a unique logical token share.

3.2 Strength of authentication mechanisms

Authentication mechanism	Type of authentication	Strength of Mechanism
Smartcard	Identity based	<p>A logical token share stored in a Smartcard or Softcard is encrypted and MAC'ed. An attacker would need to guess the encrypted share value and the associated MAC in order to be able to load a valid Logical token share into the module. This requires, as a minimum, guessing a 256-bit HMAC-SHA256 value, which gives a probability of 2^{-256}. This probability is less than 10^{-6}.</p> <p>The module can process around 2^{16} commands per minute. This gives a probability of success in a one minute period of 2^{-240}, which is less than 10^{-5}.</p>
Softcard	Identity based	

Table 10 Strength of authentication table

3.3 Services

The following table describes the services provided by the Cryptographic Module and the access policy.

The Access column presents the access level given to the CSP, R for Read, W for Write, Z for Zeroise

Service	Description	Authorized roles	Access	CSPs
Big number operation Cmd_BignumOp	Performs an operation on a large integer.	Unauthenticated	-	None
Make Blob Cmd_MakeBlob	Creates a Key blob containing the key. Note that the key ACL needs to authorize the operation.	User / JSO / NSO	W	KA, KRE, KR, KJSO, KM, KNSO, LT
Buffer operations Cmd_CreateBuffer Cmd_LoadBuffer	Mechanism for loading of data into the module volatile memory. The data can be loaded in encrypted form which can be decrypted inside the module with a key that has been previously loaded.	Unauthenticated	R	KA

Service	Description	Authorized roles	Access	CSPs
Bulk channel Cmd_ChannelOpen Cmd_ChannelUpdate	Provides a bulk processing channel for encryption / decryption, MAC generation / verification and signature generation / verification.	User	R	KA
Check User Action Cmd_CheckUserAction	Determines whether the ACL associated with a key allows a specific operator defined action.	User / JSO / NSO	R	KNSO, KJSO; KA
Clear Unit Cmd_ClearUnit	Zeroises all keys, tokens and shares that are loaded into the module. Will cause the module to reboot and perform self-tests.	Unauthenticated	Z	KA, KR, Impath keys, KJSO, remote administration session keys
Set Module Key Cmd_SetKM	Allows a key to be stored internally as a Module key (KM) value. The ACL needs to authorize this operation.	NSO	W	KM
Remove Module Key Cmd_RemoveKM	Deletes a given KM from non-volatile memory.	NSO	Z	KM
Duplicate key handle Cmd_Duplicate	Creates a second instance of a Key with the same ACL and returns a handle to the new instance. Note that the source key ACL needs to authorize this operation.	User / JSO / NSO	R	KA
Enable feature Cmd_StaticFeatureEnable	Enables the service. This service requires a certificate signed by	Unauthenticated	-	None

Service	Description	Authorized roles	Access	CSPs
	the Master Feature Enable key.			
Encryption / decryption Cmd_Encrypt Cmd_Decrypt	Encryption and decryption using the provided key handle.	User	R	KA
Erase from smartcard /softcard Cmd_EraseFile Cmd_EraseShare	Removes a file or a share from a smartcard or softcard	NSO / JSO / User	-	None
Format Token Cmd_FormatToken	Formats a smartcard or a softcard.	NSO / JSO	-	None
File operations Cmd_FileCopy Cmd_FileCreate Cmd_FileErase Cmd_FileOp	Performs file operations in the module.	NSO / JSO	-	None
Firmware Authenticate Cmd_FirmwareAuthenticate	Reports firmware version, using a zero knowledge challenge response protocol based on HMAC. The protocol generates a random value to use as the HMAC key. Note: in FIPS Level 3 mode this services is not available.	Unauthenticated	-	None
Force module to fail Cmd_Fail	Causes the module to enter a failure state.	Unauthenticated	-	None
Foreign Token open Cmd_ForeignTokenOpen	Opens a channel for direct data access to a Smartcard Requires Feature Enabled.	NSO / JSO	-	None

Service	Description	Authorized roles	Access	CSPs
Foreign Token command Cmd_ForeignTokenCommand	Sends an ISO-7816 command to a smartcard over the channel opened by ForeignTokenOpen.	Unauthenticated	-	None
Firmware Update Cmd_Maintenance Cmd_ProgrammingBegin Cmd_ProgrammingBeginChunk Cmd_ProgrammingLoadBlock Cmd_ProgrammingEndChunk Cmd_ProgrammingEnd Cmd_ProgrammingGetKeyList	Perform a firmware update. Restricted service to Entrust signed Firmware.	Unauthenticated	R	KFI
Generate prime number Cmd_GeneratePrime	Generates a random prime number.	Unauthenticated	R, W	DRBG internal state
Generate random number Cmd_GenerateRandom	Generates a random number from the Approved DRBG.	Unauthenticated	R, W	DRBG internal state
Get ACL Cmd_GetACL	Get the ACL of a given key.	User	R	KA
Get key application data Cmd_GetAppData	Get the application data field from a key.	User	R	KA
Get challenge Cmd_GetChallenge	Get a random challenge that can be used in fresh certificates.	Unauthenticated	R, W	DRBG internal state
Get KLF2 Cmd_GetKLF2	Get a handle to the Module Long Term (KLF2) public key.	Unauthenticated	-	None
Get Key Information Cmd_GetKeyInfo Cmd_GetKeyInfoEx	Get the type, length and hash of a key.	NSO / JSO / User	R	KA
Get module signing key Cmd_GetKML	Get a handle to the KML public key.	Unauthenticated	R	KML

Service	Description	Authorized roles	Access	CSPs
Get list of slot in the module Cmd_GetSlotList	Get the list of slots that are available from the module.	Unauthenticated	-	None
Get Logical Token Info Cmd_GetLogicalTokenInfo Cmd_GetLogicalTokenInfoEx	Get information about a Logical Token: hash, state and number of shares.	NSO / JSO / User	R	LT
Get list of module keys Cmd_GetKMLList	Get the list of the hashes of all module keys and the KNSO.	Unauthenticated	R	KM, KNSO
Get module state Cmd_GetModuleState	Returns unsigned data about the current state of the module.	Unauthenticated	-	None
Get real time clock Cmd_GetRTC	Get the current time from the module Real Time Clock.	Unauthenticated	-	None
Get share access control list Cmd_GetShareACL	Get the Share's ACL.	NSO / JSO / User	R	Share Key
Get Slot Information Cmd_GetSlotInfo	Get information about shares and files on a Smartcard that has been inserted in a module slot.	Unauthenticated	-	None
Get Ticket Cmd_GetTicket	Get a ticket (an invariant identifier) for a key. This can be passed to another client or to a SEE World which can redeem it using Redeem Ticket to obtain a new handle to the object.	NSO / JSO / User	-	None
Initialize Unit Cmd_InitializeUnit Cmd_InitializeUnitEx	Causes a module in the pre-initialization state to enter the initialization state. When the	Unauthenticated	Z	KA, KRE, KR, KJSO, KM, KAL, KML, KNSO, LT

Service	Description	Authorized roles	Access	CSPs
	module enters the initialization state, it erases all Module keys (KM), the module's signing key (KML), and the hash of the Security Officer's keys, HKNSO. It then generates a new KML and KM.			
Insert a Softcard Cmd_InsertSoftToken	Allocates memory on the module that is used to store the logical token share and other data objects.	Unauthenticated	R	Share Key
Remove a Softcard Cmd_RemoveSoftToken	Removes a Softcard from the module. It returns the updated shares and deletes them from the module's memory.	Unauthenticated	Z	Share Key
Impath secure channel Cmd_ImpathGetInfo Cmd_ImpathKXBegin Cmd_ImpathKXFinish Cmd_ImpathReceive Cmd_ImpathSend	Support for Impath secure channel. Requires Feature Enabled.	NSO / JSO / User	R, W	KML, Impath keys
Key generation Cmd_GenerateKey Cmd_GenerateKeyPair	Generates a cryptographic key of a given type with a specified ACL. It returns a handle to the key. Optionally, it returns a KML signed certificate with the hash of the key and its ACL information.	NSO / JSO	R, W	KML, DRBG internal state, KA, KJSO,

Service	Description	Authorized roles	Access	CSPs
Key import Cmd_Import	Loads a plain text key into the module. If the module is initialized in FIPS level 3 mode, this service is available for public keys only.	NSO / JSO	R	KA, KJSO
Derive Key Cmd_DeriveKey	Performs key wrapping, unwrapping, transport, exchange and derivation. The ACL needs to authorize this operation.	NSO / JSO / User	R, W	KA, KJSO
Load Blob Cmd_LoadBlob	Load a Key blob into the module. It returns a handle to the key suitable for use with module services.	NSO / JSO / User	W	KA, KRE, KR, KJSO, KM, KNSO
Load Logical Token Cmd_LoadLogicalToken	Initiates loading a Logical Token from Shares, which can be loaded with the Read Share command.	Unauthenticated	-	None
Generate Logical Token Cmd_GenerateLogicalToken	Creates a new Logical Token with given properties and secret sharing parameters.	NSO / JSO	W	KM, LT, KJSO
Message digest Cmd_Hash	Computes the cryptographic hash of a given message.	Unauthenticated	-	None
Modular Exponentiation Cmd_ModExp Cmd_ModExpCrt Cmd_RSALmmmedVerifyEncrypt Cmd_RSALmmmedSignDecrypt	Performs a modular exponentiation (standard or CRT) on values supplied with the command.	Unauthenticated	-	None

Service	Description	Authorized roles	Access	CSPs
Module hardware information Cmd_ModuleInfo	Reports detailed hardware information.	Unauthenticated	-	None
No Operation Cmd_NoOp	No operation.	Unauthenticated	-	None
Change Share Passphrase Cmd_ChangeSharePIN Cmd_ChangeShareGroupPIN	Updates the passphrase of a Share.	NSO / JSO / User	R, W	Share Keys
NVRAM Allocate Cmd_NVMemAllocate	Allocation in NVRAM.	NSO / JSO	-	None
NVRAM Free Cmd_NVMemFree	Deallocation from NVRAM.	NSO / JSO	-	None
Operation on NVM list Cmd_NVMemList	Returns a list of files in NVRAM.	Unauthenticated	-	None
Operation on NVM files Cmd_NVMemOp	Operation on an NVRAM file.	Unauthenticated		None
Key export Cmd_Export	Exports a key in plain text. Note: in FIPS level 3 mode, only public keys can be exported.	NSO / JSO / User	R	KA
Pause for notifications Cmd_PauseForNotifications	Wait for a response from the module.	Unauthenticated		None
Read file Cmd_ReadFile	Reads data from a file on a Smartcard or Softcard. The ACL needs to authorize this operation.	NSO / JSO	-	None
Read share Cmd_ReadShare	Reads a share from a Smartcard or Softcard. Once a quorum of shares have been loaded, the module re-	NSO / JSO / User	R	Share Keys, LT

Service	Description	Authorized roles	Access	CSPs
	assembles the Logical Token.			
Send share to remote slot Cmd_SendShare	Reads a Share and encrypts it with the Impath session keys for transmission to the peer module.	NSO / JSO / User	R	Impath Keys, Share Keys
Receive share from remote slot Cmd_ReceiveShare	Receives a Share encrypted with the Impath session keys by a remote module.	NSO / JSO / User	R	Impath Keys, Share Keys
Redeem Ticket Cmd_RedeemTicket	Gets a handle in the current name space for the object referred to by a ticket created by Get Ticket.	NSO / JSO / User	-	None
Remote Administration Cmd_DynamicSlotCreateAssociation Cmd_DynamicSlotExchangeAPDUs Cmd_DynamicSlotsConfigure Cmd_DynamicSlotsConfigureQuery Cmd_VerifyCertificate	Provides remote presentation of Smartcards using a secure channel between the module and the Smartcard.	NSO / JSO / User	R, W	Remote administration session keys
Destroy Cmd_Destroy	Remove handle to an object in RAM. If the current handle is the only one remaining, the object is deleted from RAM.	Unauthenticated	Z	KA, KJSO, KNSO, LT
Report statistics Cmd_StatGetValues Cmd_StatEnumTree	Reports the values of the statistics tree.	Unauthenticated	-	None
Show Status Cmd_NewEnquiry	Report status information.	Unauthenticated	-	None

Service	Description	Authorized roles	Access	CSPs
Secure Execution Engine Cmd_CreateSEEWORLD Cmd_GetWorldSigners Cmd_SEEJob Cmd_SetSEEMachine Cmd_TraceSEEWORLD	Creation and interaction with SEE machines.	NSO / JSO	-	None
Set ACL Cmd_SetACL	Replaces the ACL of a given key with a new ACL. The ACL needs to authorize this operation.	NSO / JSO / User	W	KA
Set key application data Cmd_SetAppData	Writes the application information field of a key.	User	W	KA
Set NSO Permissions Cmd_SetNSOPerms	Sets the NSO key hash and which permissions require a Delegation Certificate.	NSO	-	None
Set real time clock Cmd_SetRTC	Sets the Real-Time Clock value.	NSO / JSO	-	None
Signature generation Cmd_Sign	Generate a digital signature or MAC value.	NSO / JSO / User	R	KA, KNSO, KJSO
Sign Module State Cmd_SignModuleState	Returns a signed certificate that contains data about the current configuration of the module.	Unauthenticated	R	KML
Signature verification Cmd_Verify	Verifies a digital signature or MAC value.	NSO / JSO / User	R	KA
Write file Cmd_WriteFile	Writes a file to a Smartcard or Softcard.	NSO / JSO	-	None

Service	Description	Authorized roles	Access CSPs	
Write share Cmd_WriteShare	Writes a Share to a Smartcard or Softcard.	Unauthenticated	-	None

Table 11 Service table

4 Physical Security

The product is a multi-chip embedded Cryptographic Module, as defined in FIPS 140-2. It is enclosed in a hard and opaque epoxy resin which meets the physical security requirements of FIPS 140-2 level 3.

Note: The module hardness testing was only performed at a single temperature and no assurance is provided for Level 3 hardness conformance at any other temperature.

To ensure physical security, the module should be inspected periodically for evidence of tamper attempts:

- Examine the entire PCIe board including the epoxy resin security coating for obvious signs of damage.
- Examine the heat sink on top of the module and also the potting which binds the edges of the heat sink for obvious signs of damage.
- Examine the smartcard reader and ensure it is directly plugged into the module or into the port provided by any appliance in which the module is integrated and the cable has not been tampered with.

The module has a clear button. Pressing this button puts the module into the self-test state, clearing all stored key objects, Logical Tokens and impath keys and running all self-tests. The long term security critical parameters, NSO's key, module keys and module signing key can be cleared by returning the module to the factory state.

5 Rules

This section describes how to accept, initialise and operate the module in the FIPS approved mode.

5.1 Delivery

The nShield Cryptographic Module is sent to the customers using a standard carrier service. After accepting the delivery of the module, the Crypto Officer shall perform a physical inspection of the module (refer to Physical Security). This inspection is done to ensure that the module has not been tampered with during transit. If the inspection results indicate that the module has not been tampered with, the Crypto Officer can then proceed with installation and configuration of the module.

The module must be installed and configured according to the User Guides and the Initialization procedures described below.

5.2 Initialization procedures

To configure the Cryptographic Module in FIPS approved mode, the following steps must be followed:

1. Put the module in pre-initialization mode.
2. Create a FIPS 140-2 level 3 compliant Security World using Entrust supplied utility `new-world` and setting the mode to `fips-140-2-level-3`.
3. Put the module in Operational mode.

An operator can verify that the module is configured in FIPS approved mode with the command line utility `enquiry`, which reports the following active modes:

```
active modes          UseFIPSAprovedInternalMechanisms AlwaysUseStrongPrimes
FIPSLevel3Enforcedv2 StrictSP80056Ar3
```

or

```
active modes          UseFIPSAprovedInternalMechanisms FIPSLevel3Enforcedv2
StrictSP80056Ar3
```

5.3 Creation of new Operators

New User

To create a new User, the following steps must be followed:

1. Authenticate as NSO or JSO role.
2. Create a new Logical Token, LTU.
3. Split the LTU into one or more smartcards or a Softcard.
4. Generate a new Application key with the ACL configured so that the key can only be blobbed under LTU.
5. Generate a Key Blob for the Application key protected by LTU.
6. Give to the Operator the Key Blob, the Operator Cards or Softcard.

New Junior Security Officer (JSO)

To create a new JSO, the following steps must be followed:

1. Authenticate as NSO or JSO role.
2. Generate a new Logical Token, LTJSO.
3. Split LTJSO into one or more smartcards or Softcard.
4. Generate a new asymmetric key pair (KJSOpriv, KJSOpub):
 - a. Set the ACL of KJSOpriv to allow Sign and UseAsSigningKey,
 - b. Set the ACL of KJSOpub to allow ExportAsPlain
5. Generate a Key Blob for KJSOpriv protected by LTJSO
6. Export KJSOpub.
7. Create a Delegation Certificate signed by NSO or an already existing JSO, which includes KJSOpriv as the certifier and authorises the following actions
 - a. OriginateKey, which authorises generation of new keys,
 - b. GenerateLogToken, which authorises the creation of new Logical Tokens,
 - c. ReadFile, WriteFile,
 - d. FormatToken.
8. Give the Operator the Certificate, the Key Blob, the smartcards or Softcard.

6 Self tests

The Cryptographic Module performs power-up and conditional self-tests. It also supports power-up self-tests upon request by resetting the module, either by pressing the Clear button or by sending the Clear Unit command.

In the event of a self-test failure, the module enters an error state which is signalled by the SOS morse pattern flashing in the output LED. While in this state, the module does not process any commands.

6.1 Power-up self-tests

In the self-test state the module clears the RAM, thus ensuring any loaded keys or authorization information is removed and then performs the following:

- Power-up self-test on hardware components,
- Firmware integrity verification,
- Cryptographic self-tests as specified below.

Algorithm	Description
Boot Loader	
SHA512	Known Answer Test
ECDSA	Known Answer Test (verification only) with curve P-521
Firmware	
AES	Known Answer Test: ECB encryption and decryption with 128, 192 and 256-bit keys
AES CMAC	Known Answer Test: 128-bit key
SHA1	SHA1 KAT test, other size are tested along with KAT HMAC
HMAC with SHA1, SHA224, SHA256, SHA384, SHA512	Known Answer Test
RSA	Known Answer Test: sign/verify, encrypt/decrypt with 2048-bit key Pair-Wise consistency test: sign/verify
DSA	Known Answer Test: sign/verify with 2048-bit key Pair-Wise consistency test: sign/verify
ECDSA	Pair-Wise consistency test: sign/verify with curves P-224 and B-233
Key Agreement	Shared Secret Computation Known Answer Test DH

Algorithm	Description
Key Agreement	Shared Secret Computation Known Answer Test for ECDH with curves P-384 and B-233
One-step KDF	Known Answer Test with SHA-256 auxiliary function
Two-step KDF	Known Answer Test with HMAC-SHA256 auxiliary function
KBKDF	Known Answer Test
DRBG	Health Tests according to SP 800-90A
Other	
Entropy source	SP800-90B section 4.4 health tests: adaptive proportion test and repetition count test

Table 12 Cryptographic algorithm self-tests

6.2 Conditional self-tests

The module performs pair-wise consistency checks when RSA, DSA and ECDSA keys are generated and the continuous test on the entropy source.

6.3 Firmware load test

The Cryptographic Module supports firmware upgrades in the field, with authenticity, integrity and roll-back protection for the code. Entrust provides signed firmware images with the Firmware Integrity Key.

The module performs the following actions before replacing the current image:

- Code signature verification with the public Firmware Integrity Key.
- Image decryption with the Firmware Confidentiality Key.
- Verification that the Version Security Number (VSN) of the new image is not less than the VSN of the current image.

Note: updating the firmware to a non-FIPS validated version of the firmware will result in the module operating in a non-Approved mode.

Contact Us

Web site	https://www.entrust.com
Support	https://nshieldsupport.entrust.com
Email Support	nShield.support@entrust.com
Online documentation:	Available from the Support site listed above.

You can also contact our Support teams by telephone, using the following numbers:

Europe, Middle East, and Africa

United Kingdom: +44 1223 622 444
One Station Square
Cambridge
CB1 2GA
UK

Americas

Toll Free: +1 833 425 1990
Fort Lauderdale: +1 954 953 5229
Sawgrass Commerce Center – A
Suite 130,
13800 NW 14 Street
Sunrise
FL 33323 USA

Asia Pacific

Australia: +61 9126 9070
World Trade Centre Northbank Wharf
Siddeley St
Melbourne VIC 3005
Australia

Japan: +81 50 3196 4994

Hong Kong: +852 3008 4994
31/F, Hysan Place
500 Hennessy Road
Causeway Bay
Hong Kong

To get help with
Entrust nShield HSMs

nShield.support@entrust.com
nshieldsupport.entrust.com

ABOUT ENTRUST CORPORATION

Entrust keeps the world moving safely by enabling trusted identities, payments and data protection. Today more than ever, people demand seamless, secure experiences, whether they're crossing borders, making a purchase, accessing e-government services or logging into corporate networks. Entrust offers an unmatched breadth of digital security and credential issuance solutions at the very heart of all these interactions. With more than 2,500 colleagues, a network of global partners, and customers in over 150 countries, it's no wonder the world's most entrusted organizations trust us.



ENTRUST

SECURING A WORLD IN MOTION